

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Wyandotte

Location listed as:

Section-Township-Range: 22-50N-33W

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): NW NW SE

Location changed to:

35-10S-25E

E2 SW NW SW

Other changes: Initial statements: _____

Changed to: _____

Comments: _____

verification method: Map of well locations from owner, and
North Kansas City 1:24,000 topo. map.

initials: _____ date: _____


submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

P2355

1 LOCATION OF WATER WELL: County: Wyandotte	Fraction NW 1/4 NW 1/4 SE 1/4	Section Number 22	Township Number T 50N S	Range Number R 33 EW
---	---	-----------------------------	-----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?
2029 Fairfax RCKS 66115

2 WATER WELL OWNER: RR#, St. Address, Box # : 1218 Phillips Bldg 4205 Keeler AVE City, State, ZIP Code : Barbersville OK 74004	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering P12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well P2355
---	---

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 15 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 29" in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 2 Chip 1 Cement 9" out Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Silty Clay			
5	35	Silty Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-2-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 704 This Water Well Record was completed on (mo/day/yr) 11-2-04 under the business name of MAX'S by (signature) David Smith

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.



PROJECT NUMBER 321564.SI.01	BORING NUMBER PZ-355	SHEET 1 OF 1
--------------------------------	-------------------------	--------------

SOIL BORING LOG

PROJECT : Conoco Phillips - Supplemental SI	NORTHING: 309298.72	EASTING: 2276082.12
ELEVATION : 748.74 ft b.t.o.c.	DRILLING CONTRACTOR : Max's Enterprises Inc.	
DRILLING METHOD AND EQUIPMENT USED CME 750	LOGGER : E. Molander	
WATER LEVELS : 28'-29' bgs	START : 11/02/04 0730	END : 11/02/04 0745

DEPTH BELOW SURFACE (FT)	INTERVAL (FT)		STANDARD PENETRATION TEST RESULTS 6"-6"-6" (N)	SOIL DESCRIPTION SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY, OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY.	COMMENTS DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS, AND INSTRUMENTATION. Notes
	RECOVERY (FT)	#/TYPE			
0				0.0': Unconsolidated gravel fill with sand and clay, brown, moist, well graded	
2				2.0': Silty clay with sand and gravel (CL), moist	
5				5.0': Silty clay with fine sand and trace gravel (CL), gray to brown, moist	
7				7.0': Silty sand with clay and trace gravel (SM-SC), brownish gray, moist	
9				9.0': Sandy elastic silt (MH), moist, clay content increase with depth	
13				13.0': Elastic silt (MH), dark gray, moist, soft, slight odor	
15				15.0': Same as 13', darker gray, increased moisture and clay content	
16				16.0': Silty sand (SM), gray, moist, fine, odor	
18				18.0': Dark gray, strong odor	
21				21.0': Poorly graded sand (SP), brownish gray, moist, odor	
28				28.0': Encounter water	
30				30.0': Increasing gray coloration	
35				35.0': End of boring	

