CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

Location listed as:	County: Wyan dotte Location changed to:					
Section-Township-Range: 22-50N-33W	35-105-25E					
Fraction (1/4 1/4 1/4): NW SW SW	NE SW NW SW					
Other changes: Initial statements:						
Changed to:						
Comments:						
verification method: Map of well locations North Kansas City 1:24,000	from owner, and					
North Kansas City 1:24,000						
,	initials: OR 1 date: 9/9/2005					

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367. Pz 356

- · - ~				ı	_ ,						
		TER WELL:	TER WELL RE Fraction		rm WWC-5		1212 ID No ction Number	Township N	lumber	Range Nur	
County:	Nvan	dotte	$N\omega_{\nu}$	5W 1/4	SWI	i	22	T 50	N s	в <i>33</i>	E(W)
		from nearest to		address of we	ell if located v	vithin city?					
2 WATER	29 F	air fax NER: Conoc	RCKS	ins Ca	115					•	
	ddress, Box	# 1216 f	Phillips 1	Bidg 4	26 S	Recler	- AUE	Board of Ag		ivision of Water F	lesources
3 LOCATE	WELL'S LC	CATION WITH	4 DEPTH OF	COMPLETED	WELL	~	ft. ELEVAT	TION:			
	N SECTION		Depth(s) Grou		ountered 1		ft.	2	ft. 3		ft.
Г	N N	1						e measured on me			
	1	1						after after			
-	-NW -	- NE	WELL WATER			ublic water		8 Air conditioning	g 11 İn	ection well	
	x	¦	1 Domesti			il field wate		9 Dewatering	D12 0	ther (Specify belo	ow)
w	ı	- 	2 Irrigation	n 4 Indus	strial 7 D	omestic (lav	wn & garden) 🕻	Monitoring wel		عر.جــح	
	1	1						1.			
-	-sw -	- SE		al/bacteriolog	ical sample s	ubmitted to		es No		o/day/yrs sample No	
	·	i	mitted				VV	ater Well Disinfect	eu? Yes	INC	, .
	S										
		CASING USED:		5 Wrought		8 Concr				d Clampe	
1 Stee		3 RMP (S 4 ABS	н)	6 Asbestos 7 Fiberglas			(specify below)) 		ed aded 	
		2	in. to					ft., Di			
	•	and surface	<i>39u</i>	in., weig	ght			lbs./ft. Wall thickn	ess or guag	e No. 5 Ch. 9	10
		R PERFORATIO		•	-	0			bestos-Cem		
1 Ste	el	3 Stainles		5 Fibergla			MP (SR)				
2 Bra	SS	4 Galvani	zed Steel	6 Concrete	e tile	9 AE	3S	12 No	ne used (op	en hole)	
SCREEN	OR PERFOR	RATION OPENII				ed wrapped		8 Saw cut		11 None (open	hole)
	ntinuous slot		Mill slot		6 Wire v 7 Torch			9 Drilled holes 10 Other (specif			ft
	vered shutte		Key punched	25					• •		
SCREEN-	PERFORAI	ED INTERVALS	: From		ft. to	. 	ft., From		tt. to		π. ft
	GRAVEL PA	CK INTERVALS	S: From	35	ft. to	/3	ft., From		ft. to		ft.
			From		ft. to		ft., From		ft. to		ft.
6 GPOI	JT MATERIA	Al: 1 Nos	at cement	@Ceme	nt arout	3 Ben	tonito	1 Other			
Grout Inte						,	\sim	ft., From			
		urce of possible		•	10111		10 Livest			bandoned water	
	otic tank		ral lines		7 Pit privy		11 Fuels	•		il well/Gas well	
	wer lines	5 Ces			8 Sewage la	agoon			16 Other (specify below)		
		9 Feedyard	13 Insecticide storage		-						
Direction f	rom well?				,		How man	y feet?			
FROM	TO		LITHOLOG	IC LOG	-	FROM	то	PL	UGGING IN	TERVALS	
0	9	Bond	las								
9	16	Brns	sufy 5	nd							
16	35	Rin	Sand	(/ - /							
		2									
											2.0
7		1			***************************************						
CONTF	RACTOR'S	OR LANDOWNE	R'S CERTIFIC	ATION: This v	vater well wa	s (1) constr	ucted, (2) reco	enstructed, or (3)	plugged und	er my jurisdiction	and was
	on (mo/day/		-25-07					cord is true to the b d on (mo/day/yr) ,		owiedge and beli	er. Kansas
	contractor sousiness nar		11 sr c		. mis vvater t	vven necord	·	a on (mo/day/yr) , signature)	INT	The self	775
			en. PLEASE PRESS	FIRMLY and PRIN	VT clearly. Please	fill in blanks. un		correct an wers. Send t	top three conies	to Kansas Department	t of Health

INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct an wers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each <u>constructed</u> well.



 PROJECT NUMBER
 BORING NUMBER

 321564.SI.01
 PZ-356
 SHEET 1 OF 1

SOIL BORING LOG

PROJE	CT : Conocc	Phillips -	 Supplem 	ental SI	NORTHING: 309515.23	EASTING: 2276110.27				
ELEVATION: 748.19 ft b.t.o.c.					DRILLING CONTRACTOR : Max's Enterprises Inc.					
DRILLING METHOD AND EQUIPMENT USED CME 750					LOGGER: C. Morris					
WATER LEVELS : 28' bgs				START: 11/23/04 1105	END: 11/23/04 1125					
DEPTH	PEPTH BELOW SURFACE (FT)			STANDARD	SOIL DESCRIPTION	COMMENTS				
	INTERVAL (FT)		PENETRATION							
		RECOVE	RY (FT)	TEST	SOIL NAME, USCS GROUP SYMBOL, COLOR,	DEPTH OF CASING, DRILLING RATE,				
	#/TYPE		RESULTS	MOISTURE CONTENT, RELATIVE DENSITY,	DRILLING FLUID LOSS,					
		1		6"-6"-6"	OR CONSISTENCY, SOIL STRUCTURE,	TESTS, AND INSTRUMENTATION.				
		1	1	(N)	MINERALOGY.	Notes				
				(1.7)	0.0': Clay and gravel fill, brown, moist, stiff,					
_	l				no plasticity	·				
	No Soil San	npling								
					-					
_					_	_				
-						-				
5										
,					_					
_					6.0': Gray, increasing clay content, medium					
					plasticity					
					-					
_					_					
i -					9.0': Sandy silt with clay (ML), dark grayish brown,mosit, soft, slight HC odor	· · · · -				
10					most, sort, signt HC oddi					
'°					_	-				
_					11.0': Silty sand (SM), dark olive gray, moist,	_				
					slight HC odor					
_					-	· -				
_					13.0': Poorly graded sand (SP), tan to gray,	_				
					moist, trace silty nodules, slight odor	·				
_					-					
15										
, ,					_					
_					_					
_					-	-				
_					18.0': Poorly graded sand (SP), dark tan to gray,					
					moist to wet, slight HC odor					
_					-	.				
20										
						_				
_					-	_				
_					-					
					23.0': Silty sand (SM), dark grayish brown, moist,					
					fine to coarse, HC odor					
					-	·				
25										
					_	<u> </u>				
_					26.0': Poorly graded sand with silt (SP-SM), grayish					
					brown, moist to wet, HC odor	· ·				
					29.0': Poorly graded sand (SP), brownish gray, wet to _ saturated, slight HC odor					
					31.0': Grading coarser					
_					34.0': Poorly graded sand with gravel (SP),	· · · · · · · · · · · · · · · · · · ·				
_					brownish gray, coarse sand, rounded gravel,					
_					some black pieces					
35					35.0': End of boring					

