WA	TER WELL RECO	ORD Form WWC-5	KSA 82a-	1212 ID No	o. INPE 2	Y			
1 LOCATION OF WATER WELL:	Fraction	7.1.5		ction Number	Township Num		Range Nun	nber	
County: Wyandoth	10W 1/4	04) 1/4	1/4	<i>35</i>	T - 10	s	R 25	(E)W	
Distance and direction from nearest to	wn or city street ac	dress of well if located	within city?		_				
401 E. Wonavan Rd.	_ kanses	Cotes							
2 WATER WELL OWNER: MOLDE	Man kan	sas City Ton	minal						
RR#, St. Address, Box # : 40	E. Donova	en Rd.			Board of Agric	culture, Div	vision of Water R	esources	
City, State, ZIP Code : Kanso	is cite.	KS (0/0/15			Application N				
3 LOCATE WELL'S LOCATION WITH	4 DEPTH OF CO	MPLETED WELL	37.5	ft. ELEVA	TION:741.3	3			
AN "X" IN SECTION BOX:	Depth(s) Ground	lwater Encountered	1	ft.	. 2	ft. 3		ft.	
l N		WATER LEVEL							
		p test data: Well water							
NW NE		gpm: Well wate			aner8 Air conditioning			gpm	
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering (12) Other (Specify, below)								
W	2 Irrigation	4 Industrial 7	Domestic (lav	vn & garden)	10 Monitoring well	Hiv.	Sparge [Sol	Ινορ	
						Extra	action Well	2	
SW SE	Was a chemical/	bacteriological sample	submitted to	Department? Y	res No . <b>X</b> 0:				
1 1 1	mitted	<b>3</b>		Wa	ater Well Disinfected	? Yes	No		
S							,—	-	
5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concre	ata tila	CASING IOIN	TS: Glued	Clamped	٠	
1 Steel 3 RMP (SI	R)	6 Asbestos-Cement		(specify below)			d		
(2)PVC 4 ABS_	,	7 Fiberglass			·		ded <b>)/</b>		
Blank casing diameter	in. to	3.40 ft., Dia	4	in. to	} <i>Q</i> ft., Dia		in. to	.,ft.	
Casing height above land surface		in., weight			lbs./ft. Wall thickness	or guage	No. Sch.	10	
TYPE OF SCREEN OR PERFORATION	N MATERIAL:		(7)PV		10 Asbes	stos-Ceme	nt		
1 Steel 3 Stainles		5 Fiberglass		MP (SR)					
2 Brass 4 Galvaniz		6 Concrete tile	9 AB	IS	12 None	used (ope	n hole)		
SCREEN OR PERFORATION OPENIN	NGS ARE:	5 Guaz	zed wrapped		8 Saw cut		11 None (open h	nole)	
	fill slot	6 Wire	wrapped	6	9 Drilled holes				
2 Louvered shutter 4 K	ey punched	( ) ( ) 7 Torch	27 A	(41)	10 Other (specify)		00.0	π.	
SCREEN-PERFORATED INTERVALS:		ft. to	5/20	ft., From	8.0	ft. to	28.0	ft.	
GRAVEL PACK INTERVALS	From	ft. to ft. to	27.5	ft., From	/_ /	ft. to	-29 0	ft.	
GHAVEL FACK INTERVALS	From	ft. to		ft From		ft to		ft	
				, 1 10111		10			
6 GROUT MATERIAL: 1 Nea	t cement	2 Cement grout	3 Bent		Other				
Grout Intervals: From	ft. to 33.	<i>Q</i> ft., From <i>I</i> .	<i>e.O</i> ft. t	o 6.0	ft., From		. ft. to	ft.	
What is the nearest source of possible contamination:				10 Livestock pens		14 Abandoned water well			
1 Septic tank 4 Lateral lines		7 Pit privy		(11)Fuel storage		15 Oil well/Gas well			
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit		9 Feedyard		13 Insect	icide storage				
Direction from well?				How man	y feet?				
FROM TO	LITHOLOGIC	LOG	FROM	то	PLUG	GING INT	ERVALS		
	See at	rached							
	Geologic	loa							
	2.00.0	7							
								1.1	
7 CONTRACTOR'S OR LANDOWNE	R'S CERTIFICATI	ON: This water well w	as (1) constru	icted (2) reco	netructed or (3) plus	agod unde	r my juriediction	and was	
completed on (mo/day/year)	5/26/0	f	as (1) constit	and this rec	cord is true to the best	of my kno	wledge and helie	f Kansas	
Water Well Contractor's Licence No	Los	8This Water	Well Record	was completed	d on (mo/dav/vr)	7/3	19/14	I turious	
under the business name of Pour			$\sim$		signature)	7			
INSTRUCTIONS: Use typewriter or ball point pe	INDITED /	MLY and PRINT clearly, Please	e fill in blanks upr	<u> </u>	• , -	aree copies to	Kansas Department	of Health	
and Environment, Bureau of Water, Geology Serecords. Fee of \$5.00 for each constructed well.	ction, 1000 SW Jackson	St., Suite 420, Topeka, Kansa	s 66612-1367. Tel	lephone 785-296-55	522. Send one to WATER W	ELL OWNER	and retain one for you	ur	

## **GEOLOGIC LOG** OWNER: Magellan Pipeline Company, LLC LEGGETTE, BRASHEARS & GRAHAM, INC. Well Number: MPE 24 North Kansas City, Missouri PAGE <u>1</u> OF <u>1</u> PAGE(S) AS - 2" sch 40 V-wire SITE LOCATION: Kansas City Terminal SCREEN SIZE & TYPE: MPE - 4" sch 40 machine slot MPE 401 E. Donovan Road 28.0 fbg - 8.0 fbg Kansas City, KS 66115 AS - .020 AS DRAFT SLOT NO.: MPE - .010 **SETTING:** 37.0 fbg - 34.0 fbg AS - 12/20 DATE COMPLETED: 05/26/04 SAND PACK SIZE & TYPE: MPE - 16/30 MPE AS 29.0 fbg - 6.0 fbg DRILLING COMPANY: Boart Longvear **SETTING:** 37.5 fbg - 33.0 fbg AS - 2" sch 40 PVC MPE - 4" sch 40 PVC CASING SIZE & TYPE: MPE DRILLING METHOD: Hollow Stem Auger **SETTING:** 34.0 fbg - +6.0'ag 8.0 fbg - +2.0'ag AS - 1/4" bentonite time release pellets SAMPLING METHOD: SEAL TYPE: MPE - 3/8" Bentonite Chips AS MPE 6.0 fbg - 1.0 fbg OBSERVER: Susan Sweet SETTING: 33.0 fbg - 29.0 fbg REFERENCE POINT (RP) Grade BACKFILL TYPE: STATIC WATER LEVEL: ELEVATION OF RP: 741.53 STICK-UP: AS 6.0' MPE 2.0' DEVELOPMENT METHOD: SURFACE COMPLETION: **DURATION:** YIELD: REMARKS: ABBREVIATIONS: MC=MACRO CORE W=WASH C=CUTTINGS G=GRAB ST=SHELBY TUBE REC=RECOVERY PPM=PARTS PER MILLION FBG=FEET BELOW GRADE RECOVERED PID READING **DEPTH** (Feet) SAMPLE DESCRIPTION **TYPE** (Feet) (ppm) **FROM** TO 0 6 Open bore hole. 6 8 CLAY, medium brown; moist. Slight odor. 8 22 SAND, fine and medium; olive-brown; dry. Strong odor. 22 28 SAND, medium; some organic material; medium gray; wet. Strong odor. 28 37.5 SAND, medium; little coarse; some organic material; saturated. Strong odor.

