	WA	TER WELL REC	ORD	Form WWC-	5 KSA 8	32a-1212	ID N	o. 446	2-27	4 Mu	105-	.09	
1 LOCATION OF WATE		Fraction 1/4	WH	1/4	1/4	Section I		Tov	wnship N		P	lange Nu 25	
Distance and direction fro	m nearest tov	wn or city street a	address o	of well if locate	ed within cit	y?	_	·	•	<u> </u>	- 11		
401	E Don	lovan P	<u>-d.</u>	Kans	as Ci	44 ' K	_ح_	Idell	5				
2 WATER WELL OWNE RR#, St. Address, Box #	H: Mage	1197 Pipa	line	Compar	Y	•		_					
City, State, ZIP Code	: 401 E	s Culy	ks	ldou 5	•				pard of Ago oplication	riculture, D Number:	ivision o	of Water F	Resources
3 LOCATE WELL'S LOCA					30	ft	t. ELEVA	<u>.</u>	·				
AN "X" IN SECTION BO		Depth(s) Groun	dwater E	ncountered	1		ft	. 2		ft. 3			ft.
		WELL'S STATION	C WATER	ata: Well wa	ft. ter was	below lar	nd surfac	e measur after	ed on mo	/day/yr hours p	umping		apm
	NE	Est. Yield	g	pm: Well wa	ter was		ft. a	after		hours p	umping .		
	1	WELL WATER 1 1 Domestic			5 Public wa 6 Oil field w		•		nditioning tering		ijection v other (Sc	well ecify belo	ow)
w	1 E	2 Irrigation	4 Ir		7 Domestic			O Monite	oring well				
1	1								N				
SW	SE	Was a chemical mitted	l/bacterio	ological sampl	e submitted	to Depa		res l ater Well I			no/day/yı	rs sample No	
	ı	milou						4101 11011	Districcte	u: 163		140	,
5 TYPE OF BLANK CAS	SING USED:		5 Wrou	ight iron	8 Co	oncrete tile	<u> </u>	CAS	SING JOI	NTS: Glue	d	. Clampe	d
1 Steel	3 RMP (SF	۲)	6 Asbe	stos-Cement	9 Ot	her (spec	ify below)		Weld	ed		
PVC Blank casing diameter	4 ABS 7	in to	7 Fiber		,								
Casing height above land	surface	2.5	in.,	weight				lbs./ft. Wa	all thickne	ess or quad	e No		
TYPE OF SCREEN OR P					C	PVC				estos-Cem			
1 Steel	3 Stainless 4 Galvaniz		5 Fiber	rglass crete tile		RMP (SI ABS	R)			er (Specify) ne used (op	,		
2 Brass SCREEN OR PERFORAT			o conc		azed wrapp			8 Saw		ie useu (op	,	ne (open	holo)
Contouous slot	3.3				re wrapped			9 Drille	ed holes			` '	,
2 Louvered shutter	4 K	ey punched	2 -		rch cut					/)			
SCREEN-PERFORATED	INTERVALS:	From	20	ft. to ft. to	17	2 !	ft., From			ft. to			ft.
GRAVEL PACK	INTERVALS:	: From	3 <i>O</i>	ft. to		1	ft., From			ft. to			ft.
		From		ft. to		1	ft., From		•••••	ft. to	•••••		ft.
6 GROUT MATERIAL:		t cement .		ment grout	ত্তা	Bentonite	5 4	1 Other					
Grout Intervals: From			ft	t., From		ft. to		ft., Fr	rom		ft. to		ft.
What is the nearest source	•							ock pens				ed water	well
 Septic tank Sewer lines 	4 Later 5 Cess			7 Pit priv8 Sewag				torage zer storag		15 C		as well ecify belo	,,,,)
3 Watertight sewer li		•		9 Feedya				ticide stora		ÄÄ		ecily beic	,w,
Direction from well?						ŀ	How man	y feet?		•			
FROM TO		LITHOLOGIC	•		FRON	/ T	0		PLU	IGGING IN	TERVAL	.S	
0 8	Open	bore ho					-+						
8 22 22 30	Sand 40	3 <11+	1 -14	y gray	<u> </u>								
		<u> </u>	we i	toaredi	7								
				1									
	# See	e attach	Men	7									
					-								
	,												
7 CONTRACTOR'S OR	LANDOWNE	R'S CERTIFICAT	ION: Th	is water well	was (1) cor	nstruct	(2) reco	nstructed	or (3) n	luaged upo	ler my ii	risdiction	and was
completed on (mo/day/year) 10 11	5 105				ar	nd this red	cord is true	e to the be	est of my kn	owledge		
Water Well Contractor's Lic		. 1		This Wat	er Well Rec	ord was o	complete	d on (mo/	day/yr)	1-4-	00		
under the business name of	~~~	+ Longye		ompan				signature)		A			
INSTRUCTIONS: Use typewrite and Environment, Bureau of W records. Fee of \$5.00 for each	ater, Geology Sec	tion, 1000 SW Jackso	n St., Suite		ase tiil in blanks sas 66612-136	s, underline o 7. Telephone	or circle the e 785-296-5	correct answ 522. Send on	ers. Send to ne to WATER	p tere copies R WELL OWNE	to Kansas R and reta	Department in one for yo	of Health our
records. Fee or \$5.00 for each	vonsudcted well.												

LE			SIC LO		OWNER: Well Number:	Magellan Pipeli MW05-09	ne Company, L.F).
	N	orth Kansas (City, Missouri		PAGE 1 OF			
SITE LOCA	ATION:	Kansas City 401 E. Done Kansas City	ovan Road		SCREEN SIZE	& TYPE:	2-inch sch 40	PVC V-wire wrap
					SLOT NO.:	0.010	SETTING:	29.5 - 10.0 fbg
DATE COM	IPLETED:	10/07/05			SAND PACK SI	ZE & TYPE:	16/30	Silica Sand
DRILLING	COMPANY	: Boart Longy	year		SETTING:	30.0 - 8.0 fbg		
		Kevin O'Bri	ian		CASING SIZE &	& TYPE:	2-inch	sch 40 PVC
DRILLING	METHOD:	4 1/4 Hollov	w Stem Auger		SETTING:	10.0 f	bg to 2.42 feet ab	ove grade
SAMPLING	METHOD:	N/A			SEAL TYPE:	3/8" Bentonite	chips	
OBSERVER	l :	Susan Swee	t		SETTING:	8.0 - 1.0 fbg		
REFERENC	CE POINT (F	RP)	South of Alcohol	l Rack	BACKFILL TY	PE: Sand		
ELEVATIO	N OF RP:	Grade			STATIC WATE	R LEVEL:	24.13 fbg	
STICK-UP:	2.42 feet abo	ve grade			DEVELOPMEN	T METHOD:	Surge with block pump.	ker; purge with whale
SURFACE (REMARKS:	COMPLETIC	ON:	3x3 concrete pad	I	DURATION:	2.0 hours	YIELD:	
ABBREVIAT	TONS: REC=RECOV	MC=MACRO	O CORE W=WA	ASH C=CUTTI	NGS G=GRA	AB ST=S	SHELBY TUBE	
DEBUT			PPM=PARTS PER			FBG=FEET BEL	OW GRADE	
DEPTI FROM	H (Feet)	SAMPLE TYPE		PID READING (ppm)			OW GRADE	
	H (Feet)	SAMPLE	RECOVERED	PID READING	Open bore hole.			
FROM	H (Feet)	SAMPLE	RECOVERED	PID READING		DESCI	RIPTION	
FROM 0	H (Feet) TO	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole.	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	
0 8	H (Feet) TO 8 22	SAMPLE TYPE	RECOVERED	PID READING	Open bore hole. SAND and SILT, fi	DESCI	RIPTION bleum odor.	

· •