•	WATER WELL RECORD	Form WWC-5	(SA 82a-1212	ID No. M	PELA	5-3	7	
1 LOCATION OF WATER WELL County: Wyan ootse			Section Nur	mber To	wnship Num	ber S	Range Nur	
Distance and direction from neare			in city?	سسد. د				
	Donaval Rd,		YIKS 6	6115				
2 WATER WELL OWNER:	gallan Pipeling	Company	•					
City, State, ZIP Code :	i E Donavan Rd 1898 Euty i K	5 66115		Α	pplication Nu	ımber:	ivision of Water F	
3 LOCATE WELL'S LOCATION W	/ITH 4 DEPTH OF COME	PLETED WELL394.	5 ft. E	LEVATION: 7	143			
AN "X" IN SECTION BOX:	Depth(s) Groundwar							
		TER LEVEL						
	Est. Yield	gpm: Well water wa	s	ft. after		hours pu	ımping	
	WELL WATER TO E		ic water supply ield water supply		onditioning aterina		jection well ther (Specify belg	w)
w			nestic (lawn & gar					
					١.		f	
SW SE		teriological sample subr	nitted to Departm					
1 1	mitted			vvater vveii	Disinfected?	res	No)
5 TYPE OF BLANK CASING US	SED: 5 V	Vrought iron	8 Concrete tile		SING IOINI	re, Cluc	d Clampe	
		9	9 Other (specify		ASING JOIN		ed	
2 PVC) 4 AB	S 7 F	iberglass	1		<u></u>	Tirea	ded	
Blank casing diameter2			•					
Casing height above land surface		in., weight		lbs./ft. W				
TYPE OF SCREEN OR PERFOR 1 Steel 3 Sta		Fiberglass	8 RMP (SR)		10 Asbes		ent 	
1 0.001		Concrete tile	9 ABS		12 None			
SCREEN OR PERFORATION OF	PENINGS ARE:	5 Guazed		8 Sav			11 None (open	hole)
1 Continuous slot	MILISIO +	Wire wra 7 Torch cut			led holes			ft
2 Louvered shutter	4 Key punched . 39	·5 ft. to 36.			` '			
SCREEN-PERFORATED INTERV								
GRAVEL PACK INTERV	/ALS: From	ft. to	: 4 ft.,	From31.		ft. to	7,2	ft.
	From	ft. to	ft.,	From		ft. t o	•••••	ft.
	Neat cement	Cement grout	3 Bentonite					
Grout Intervals: From35	4 ft. to 31.8	ft., From 7. 2	ft. to	. . ft., F	From		ft. to	ft.
What is the nearest source of pos				Livestock pens	6		bandoned water	well
· •	Lateral lines	7 Pit privy		Fael storage	~~		il well/Gas well	
	Cess pool Seepage pit	8 Sewage lago 9 Feedyard		Fertilizer stora Insecticide sto		16 0	ther (specify belo	ow)
Direction from well?	Seepage pit	9 Feedyard		w many feet?	rage			•••••
FROM TO	LITHOLOGIC LO	G	FROM TO		PLUG	GING IN	TERVALS	
	e AHachment							
	J							
	4. 4. 4. 4. 4. 4. 4. 4. 4. 4. 4. 4. 4. 4							
7 CONTRACTOR'S OR LANDO								
CONTRACTOR'S OR LANDO completed on (mo/day/year)	WHER'S CERTIFICATION	I: This water well was	1) constructed (2	 reconstructed this record is transition. 	a, or (3) plug	gged und	er my jurisdiction	n and was of Kanese
Water Well Contractor's Licence N	0 658	This Water We	II Record was con	npleted on (ma	o/day/vr)	1-4-0		ansas
	art Longgear Co			by (signature		7	•	
INSTRUCTIONS: Use typewriter or ball p	oint pen. PLEASE PRESS FIRMLY	and <u>PRINT</u> clearly. Please fill in	n blanks, underline or ci	ircle the correct ans	wers. Send top	ree copies	to Kansas Department	of Health
and Environment, Bureau of Water, Geole records. Fee of \$5.00 for each constructed		Suite 420, Topeka, Kansas 666	12-1367. Telephone 78	35-296-5522. Send	one to WATER W	VELL OWNE	:R and retain one for ye	our

	•	BRASHEA	RS & GRAHA	GEOLOGIC LOG					
SITE LOCAT	LEGGETTE, BRASHEARS & GRAHAM, INC. North Kansas City, Missouri					Well Number: MPE/AS - 37 PAGE <u>1</u> OF <u>1</u> PAGE(S)			
401		Kansas City Terminal 401 E. Donovan Road Kansas City, KS 66115			SCREEN SIZE	& TYPE: AS - 0.020 MPE - 0.010	AS - 2-inch sch MPE - 4-inch sc SETTING:	40 V-wire ch 40 machine slot AS 39.5 fbg - 36.5 fbg MPE 30.5 fbg - 10.5 fbg	
DATE COMPLETED: 10/04/05					SAND PACK SI		AS - 12/20 MPE - 16/30		
DRILLING COMPANY: Boart Longyear					SETTING:	AS 40 fbg - 35.4 fbg	MPE 31.5 fbg - 7.2 fbg	a cab 40 DVC	
Kevin O'Brian					AS - 2-inch sch 40 PVC CASING SIZE & TYPE: MPE - 4-inch sch 40 PVC AS MPE				
DRILLING METHOD: 8 1/4 Hollow Stem Auger				SETTING:	36.5 fbg - 0.5 fbg	10.5 fbg - 1.0 fbg			
SAMPLING METHOD: N/A				SEAL TYPE:	AS - 1/4-inch ben MPE - 3/8-inch B AS		se pellets		
OBSERVER:	•	Brandon Go	mer		SETTING:	35.4 fbg - 31.5 fbg			
REFERENC	E POINT (R	P)	NE corner of Boi	ler House	BACKFILL TY	PE: Sand with aspl	halt patch		
ELEVATION	N OF RP:	Grade			STATIC WATER LEVEL: N/A				
STICK-UP:					DEVELOPMENT METHOD: N/A				
SURFACE C REMARKS:	COMPLETIC	ON:	Asphalt cover un	til completed	DURATION:		YIELD:		
ABBREVIATI	IONS:	MC=MACRO	CORE W=WA	ASH C=CUTTI	NGS G=GRA	AB ST=SI	IELBY TUBE		
]	REC=RECOV	ERY	PPM=PARTS PER	MILLION		FBG=FEET BELO	W GRADE		
DEPTH FROM	(Feet) TO	SAMPLE TYPE	RECOVERED (Feet)	PID READING (ppm)	DESCRIPTION				
0	6				Open bore hole.				
6	10				CLAY (no sample))			
10	15	С			SAND, fine, some	silt, gray, dry, petrole	um odor.		
15	18	С			SAND, fine, some	silt; gray; moist; petro	oleum odor.		
18	25	С			SAND, fine, some silt; gray; wet; petroleum odor.				
25	40	С			SAND, fine to coarse, some silt; gray; wet; petroleum odor.				
			-						
							· -· .		
						·····		······································	
		l	i	l					