W	ATER WELL RECO	ORD Form WWC-	-5 KSA 82a-1	212 ID No	MPELAS	- 40	<u>) </u>	
LOCATION OF WATER WELL:	Fraction 1/4	J W 1/4		tion Number	Township Num		Range Nu	
Distance and direction from nearest to		ddress of well if locate Kansas	ed within city?		15			
2 WATER WELL OWNER: Mage	Uon Pupeli	e company	-114/ =	- UV				
RR#, St. Address, Box # : 401	2 DONOUGA		_		Board of Agric Application No	,	rision of Water	Resources
3 LOCATE WELL'S LOCATION WITH				ft. ELEVAT	ION:7.4.3			
AN "X" IN SECTION BOX:		water Encountered						
I N		WATER LEVEL						
		gpm: Well wa						
	1		5 Public water s		8 Air conditioning		ection well	
w ! ! E	1 Domestic 2 Irrigation		 Oil field water Domestic (law 		9 Dewatering10 Monitoring well	extree	er (Specify be	10W) 50919 8
· · ·	2 migation	7 modomar	, Domostio (law	ii a gaidoii,	o workering wer		••••••	
SW SE	Was a chemical/ mitted	bacteriological samp	le submitted to [es; ter Well Disinfected?		• •	le was sub- No
Ŝ								
5 TYPE OF BLANK CASING USED:		5 Wrought iron6 Asbestos-Cement	8 Concre	te tile specify below)	CASING JOIN		Clampe d	
PVC 4 ABS	,	7 Fiberglass	,				ded	
Blank casing diameter2	in. to	34. ≤ ft., Dia	4	in. to <i>L.C.</i>	ft., Dia		in. to	ft.
Casing height above land surface	-1	in., weight		l	bs./ft. Wall thickness	or guage	No	
TYPE OF SCREEN OR PERFORATION			CXPV			tos-Cemer		
1 Steel 3 Stainles 2 Brass 4 Galvani		5 Fiberglass6 Concrete tile	8 RM 9 ABS	P (SR)		(Specify) used (oper	n hole)	
2 2.400				,		٠.	,	
SCREEN OR PERFORATION OPENI 1 Continuous slot	Mill sleet	5 G∪ 6-₩1	re wrapped	ا ار	8 Saw cut 9 Drilled holes	1	11 None (open	i hole)
	Key punched	7 To	rch cut		10 Other (specify)			
SCREEN-PERFORATED INTERVALS	7	39. Cft. to	36.5	ft., From .	4" 30.5	ft. to	10.5	ft.
	From	∂ft. to ft. to	*	ft., From .		ft. to		ft.
GRAVEL PACK INTERVALS		ft. to ft. to						
	110111			11., 1 10111 .		11. 10		
	at cement	2 Cement grout	3 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3 -	Mile 4	Other			
Grout Intervals: From355		ft., From) .5	ft., From		ft. to	ft.
What is the nearest source of possible				10 Livesto	•		andoned water	
1 Septic tank 4 Late		7 Pit priv			orage			
2 Sewer lines 5 Ces	•	-	ge lagoon	12 Fertiliz	-		ner (specify bel	,
3 Watertight sewer lines 6 See Direction from well?	page pit	9 Feedy	aru	How many	cide storage		•••••	
FROM TO	LITHOLOGIC	LOG	FROM	TO		GING INTE	ERVALS	
7110	Ennocodio		17101	-10	1 200		-117/120	
Sec	= Attachin	ien +						
	- (1 () () () ()							
		·-···						
7 CONTRACTOR'S OR LANDOWNE	EDIS CEDITIONE	ON: This water"	woo(1)	otod (0) ====	notrupted as (0) =1		e man looke diest-	
CONTRACTOR'S OR LANDOWNE completed on (mo/day/year)	LOS CAMPIFICATI	ON: This water well	was (1) constru	and this roo	nstructed, or (3) plug ord is true to the boot	of my know	r my jurisdictio	in and was
Water Well Contractor's Licence No	658	This Wat	er Well Record	was completed	on (mo/dav/vr)	-4-06	Medge and bei	ici. Nailsas
under the business name of		Campany			ignature	Ż		
INSTRUCTIONS: Use typewriter or ball point p	en. PLEASE PRESS FIR	MLY and PRINT clearly. Ple	ase fill in blanks, unde			ree copies to	Kansas Departmer	nt of Health
and Environment, Bureau of Water, Geology Se records. Fee of \$5.00 for each constructed wel	ection, 1000 SW Jackson	St., Suite 420, Topeka, Kar	nsas 66612-1367. Tele	ephone 785-296-55	22. Send one to WATER W	ELL OWNER	and retain one for	your

	GEC)LOG	IC LO	G	OWNER:	Magellan Pipelin	e Company, L.P.			
LEGGETTE, BRASHEARS & GRAHAM, INC. North Kansas City, Missouri					Well Number: MPE/AS - 40 PAGE 1 OF 1 PAGE(S)					
SITE LOCA	ATION:	Kansas City 401 E. Dono Kansas City	ovan Road		SCREEN SIZE	& TYPE: AS - 0.020	AS - 2-inch sch MPE - 4-inch s	40 V-wire ch 40 machine slot AS 39.5 fbg - 36.5 fbg MPE		
					SLOT NO.:	MPE - 0.010	SETTING: AS - 12/20	30.5 fbg - 10.5 fbg		
DATE COMPLETED: 09/26/05				*****	SAND PACK SI	ZE & TYPE:	MPE - 16/30 MPE			
DRILLING COMPANY: Boart Longyear				SETTING:	40 fbg - 35.5 fbg	31.5 fbg - 8.2 fbg	h ash AO DVC			
Kevin O'Brian				CASING SIZE		MPE - 4-in	h sch 40 PVC ch sch 40 PVC			
DRILLING METHOD: 8 1/4 Hollow Stem Auger				SETTING:		MPE 10.5 fbg - 1.0 fbg				
SAMPLING	SAMPLING METHOD: N/A				SEAL TYPE:	AS - 1/4-inch ben MPE - 3/8-inch B		se pellets		
OBSERVE	₹:	Susan Swee	t		SETTING:	35.5 fbg - 31.5 fbg				
REFERENC	CE POINT (F	RP)	South of Station		BACKFILL TY	PE: Sand				
ELEVATIO		Grade			STATIC WATER LEVEL: N/A					
STICK-UP:	Flush COMPLETION	ON:	Gravel		DEVELOPMEN DURATION:	NT METHOD:	N/A YIELD:			
REMARKS:					D C L					
ABBREVIAT	TONS: REC=RECOV	MC=MACRO			NGS G=GRA	AB ST=SF FBG=FEET BELO	HELBY TUBE			
DEPTH (Feet) SAMPLE RECOVERED PID READING										
FROM 0	4	<u> </u>			Open bore hole.					
4	12	С			1	and atrong natrolous	a adaz	i		
12	27	С				soft; strong petroleum ine; olive gray; strong				
27	40	С			SAND, grades to n		g peutoteum odor.			
	40				SAND, grades to it	icarum, wet.				
<u> </u>										
L	l	<u> </u>		1	1					