•	WATER WELL RECORD	Form WWC-5	(SA 82a-1212 ID N	10. MPE/AS	- 41		
1 LOCATION OF WATER WELL: County: Wyando te		_	Section Number 3 5		mber S	Range Nu R 25	mber @ /W
Distance and direction from nearest				_			
HOLE DONOUG	an Rd, Kan	sas City, k	5 66115				
RR#, St. Address, Box # : 40	gellan Pipeline	company.		D	· II D'	1-1 (M -1 1	
City, State, ZIP Code : 140	msas city, ks	66115		Board of Agi Application I		vision of Water I	Hesources
3 LOCATE WELL'S LOCATION WI	TH 4 DEPTH OF COMPL	ETED WELL 34	5 ft. ELEV				
AN "X" IN SECTION BOX:	Depth(s) Groundwate	er Encountered 1	f	t. 2	ft. 3 .		ft.
N I	WELL'S STATIC WAT	ER LEVEL	ft. below land surfa	ce measured on mo/	day/yr	ımnina	anm
NW NE	Est. Yield	. gpm: Well water wa	s ft.	after	hours pu	mping	gpm
1 1	WELL WATER TO BE		ic water supply eld water supply	•		ection well her (Specify bel	OW)
W - 1 - 1 - E			estic (lawn & garden)				
						•	
SW SE	Was a chemical/bacte mitted	eriological sample subr		Yes No		o/day/yrs sample N	
5 TYPE OF BLANK CASING USE	=D: 5 W	rought iron	8 Concrete tile	CASING IOI	MTS: Gluoc	I Clampe	
1 Steel 3 RMP	(SR) 6 As	sbestos-Cement	8 Concrete tile 9 Other (specify below		Welde	ed	
2 PV 4 ABS					Hirea	dec	
Blank casing diameter2							
Casing height above land surface TYPE OF SCREEN OR PERFORA		i., weight	(EVQ		ss or guage estos-Ceme		
		berglass	8 RMP (SR)				
2 3.000		oncrete tile	9 ABS	12 Non-	e used (ope	en hole)	
	Millster 4	5 Guazed v Wire wran 7 Torch cut		8 Saw cut 9 Drilled holes 10 Other (specify	.	11 None (open	,
	4 Key punched	ft. to 34.	_				
SCREEN-PERFORATED INTERVA	LS: From	π. to	ft., From		ft. to	15/19	
GRAVEL PACK INTERVA		ft. to					
	From	ft. to	π., From	1	ft. to		π.
		Cement grout		4 Other			
Grout Intervals: From35. \$		ft., From 2003		ft., From			
What is the nearest source of possi		7 Diamento	10 Lives 11 uel	stock pens		pandoned water	well
1 Septic tank 4 La 2 Sewer lines 5 C	aterai iines Sess pool	7 Pit privy 8 Sewage lago		storage lizer storage		il well/Gas well ther (specify belo	nw)
3 Watertight sewer lines 6 S	•	9 Feedvard		cticide storage	10 0		
Direction from well?		,	How ma				
FROM TO	LITHOLOGIC LOG	F	ROM TO	PLU	GGING IN	TERVALS	
See	Attachment						
			- - 				
7 CONTRACTOR'S OR LANDOW	(NER'S CERTIFICATION:	This water well was) constructed (2) rec	onstructed or (3) pl	ugged und	er my jurisdiction	n and was
CONTRACTOR'S OR LANDOW completed on (mo/day/year)	7-26-05		and this re	ecord is true to the be	st of my kn	pyledge and beli	ef. Kansas
Water Well Contractor's Licence No	050	This Water Wel	Record was complete	ed on (mo/day/yr)	1-4-	שי	
under the business name of	1 7	<u></u>	la	/-!\\			
INSTRUCTIONS: Use typewriter or ball point	art Longgetr	Company		(signature)	<u>-7</u> _		

	GEC	COC	SIC LO	G	OWNER: Magella	n Pipeline Company, L.P.		
LEGGETTE, BRASHEARS & GRAHAM, INC. North Kansas City, Missouri				Well Number: MPE/AS - 41 PAGE 1 OF 1 PAGE(S)				
SITE LOCATION:		Kansas City Terminal 401 E. Donovan Road			SCREEN SIZE & TYPE	AS - 2-inch sch 40 V-wire MPE - 4-inch sch 40 machine slot AS		
Kansas City, KS 66115				AS - 0.0 SLOT NO.: MPE - 0	0.010 SETTING: 30.5 fbg - 10.5 fbg			
DATE COMPLETED: 10/05/05					SAND PACK SIZE & T	AS - 12/20 YPE: MPE - 16/30 AS MPE		
DRILLING COMPANY: Boart Longyear				SETTING: 40 fbg - 35.5 fbg 31.4 fbg - 8.5 fbg AS - 2-inch sch 40 PVC				
Kevin O'Brian					AS MPE			
DRILLING METHOD: 8 1/4 Hollow Stem Auger SAMPLING METHOD: N/A					AS - 1/4 SEAL TYPE: MPE - 3	g - 1.0 fbg 10.5 fbg - 1.0 fbg 4-inch bentonite time release pellets 8/8-inch Bentonite Chips AS MPE		
OBSERVER	R:	Susan Swee	t		l	AS MPE g - 31.4 fbg 8.5 fbg - 5.0 fbg		
REFERENC	CE POINT (R	RP)	South of Station	Building	BACKFILL TYPE: Sand			
ELEVATION OF RP: Grade				· ·	STATIC WATER LEVE	IL: N/A		
STICK-UP: Flush SURFACE COMPLETION: Gravel REMARKS:					DEVELOPMENT METI DURATION:	HOD: N/A YIELD:		
ABBREVIAT	IONS: REC=RECOV	MC=MACRO	O CORE W=WA			ST=SHELBY TUBE EET BELOW GRADE		
DEPTI FROM	H (Feet)	SAMPLE RECOVERED PID READING (ppm)			DESCRIPTION			
0					Open bore hole.			
8	12			,	CLAY			
12	26				SAND and SILT, fine; gray;	dry; strong petroleum odor.		
26	38				SAND and SILT, fine; gray;	wet; strong petroleum odor.		
38	40				Grades to medium.			
			1		ļ			
****						1. 14. DAILY B		