	WATER WELL RECORD	Form WWC-5 K	SA 82a-1212 II	D NO. 1776/45	52
1 LOCATION OF WATER WE	LL: Fraction	1	Section Numb		
County: Wyardott			35	T 10	s R 25 69/w
Distance and direction from nea	onavan Rd. Ki	nsas city		15	
2 WATER WELL OWNER: M	of E Donovan Rd	empany '		Be and of As d	W Division of Water December
	casas caty, ks	lalall		Application N	culture, Division of Water Resources umber:
3 LOCATE WELL'S LOCATION	WITH 4 DEPTH OF COMPL	ETED WELL 34.	ft. ELE		
AN "X" IN SECTION BOX:					ft. 3 ft.
N I	— WELL'S STATIC WAT	ER LEVEL	ft. below land su	rface measured on mo/d	ay/yr
1 1					. hours pumping gpn . hours pumping gpn
NW NE-	WELL WATER TO BE	USED AS: 5 Publi	c water supply	8 Air conditioning	11 njection well
			eld water supply		Other (Specify below)
W	E 2 Irrigation 4	Industrial 7 Dome	estic (lawn & garde	en) To Monitoring Well.	extraction lair sparg
SW SE-	- Was a chemical/bacte	eriological sample subm	nitted to Departmer	nt? Yes No; Water Well Disinfected	If yes, mo/day/yrs sample was sub ? Yes No
S					
5 TYPE OF BLANK CASING	USED: 5 W	rought iron 8	3 Concrete tile	CASING JOIN	TS: Glued Clamped
	RMP (SR) 6 As	bestos-Cement 9	Other (specify be	elow)	Welded
		perglass 4 Dia	:- 4-	10.5 4 00	in. toft
Casing height above land surface					s or guage No
TYPE OF SCREEN OR PERFO		., weight	CTEVE		stos-Cement
		perglass	8 RMP (SR)		(Specify)
2 Brass 4 G	Salvanized Steel 6 Co	oncrete tile	9 ABS	12 None	used (open hole)
SCREEN OR PERFORATION (1 Continuous slot	3 Mill-stot 4	Wire wrat		8 Saw cut 9 Drilled holes	11 None (open hole)
2 Louvered shutter	4 Key punched	7 Torch cut			ft
SCREEN-PERFORATED INTE	RVALS: From	ft. to	ft., Fi	rom 7	ft. to
GRAVEL PACK INTE	RVALS: From 40	ft. to 3.5 .	ft., F	rom3(3	ft. to
<u> </u>	From	ft. to	ft., F	rom	ft. toft
6 GROUT MATERIAL:	1 Neat coment	Cement grout	Contonito	4 Othor	
6 GROUT MATERIAL: Grout Intervals: From 35	Neat cement 3.3 ²	ft From 7.5	ft to S-	ft From	ft. toft
What is the nearest source of p				vestock pens	14 Abandoned water well
1 Septic tank		7 Pit privy		•	15 Oil well/Gas well
·	5 Cess pool	8 Sewage lago		ertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 ln	secticide storage	
Direction from well?			How	many feet?	
FROM TO	LITHOLOGIC LOG	F	ROM TO	PLUG	GING INTERVALS
	tersmand the second				
CONTRACTOR'S OR LAND	ONNERS CERTIFICATION:	This water well was) constructed (2)	reconstructed, or (3) plu	gged under my jurisdiction and wa
completed on (mo/day/year)	4125705		and thi	is record is true to the bes	gged under my jurisdiction and wa t of my knowledge and belief. Kansa ーヰーめ
			Record was comp	oleted on (mo/day/yr)	-4-02
under the business name of	boart Longyeur C	2MPQAY		by (signature)	7
INSTRUCTIONS: Use typewriter or ba	all point pen. <u>PLEASE PRESS FIRMLY</u> a eology Section, 1000 SW Jackson St., S	nd PRINT clearly. Please fill in	blanks, underline or circl	e the correct answers. Send top	three copies to Kansas Department of Health
records. Fee of \$5.00 for each constru		uno 720, Topena, Narisas 600	2 1007. Telephone 765-	LUG GGEE. Gend one to WATCH V	TEEE STITE I AND TELANT ONE IOI YOU

GEOLOGIC LOG LEGGETTE, BRASHEARS & GRAHAM, INC. North Kansas City, Missouri					OWNER: Magellan Pipeline Company, L.P. Well Number: MPE/AS - 52 PAGE 1 OF 1 PAGE(S)			
SITE LOCA	ATION:	Kansas City 401 E. Done Kansas City			SCREEN SIZE	& TYPE: AS - 0.020 MPE - 0.010	AS - 2-inch sch MPE - 4-inch sc SETTING:	40 V-wire ch 40 machine slot AS 39.5 fbg - 36.5 fbg MPE 30.5 fbg - 10.5 fbg
DATE COMPLETED: 09/25/05					SAND PACK SI		AS - 12/20 MPE - 16/30 MPE	30.3 10g 10.3 10g
DRILLING COMPANY: Boart Longyear Kevin O'Brian				SETTING:	40 fbg - 35.5 fbg	31.3 fbg - 7.5 fbg AS - 2-incl	h sch 40 PVC	
Kevin O'Brian DDII I INC METHOD: 8 1/4 Hollow Stem Auger				CASING SIZE & SETTING:	AS	MPE	cn scn 40 PVC	
DRILLING METHOD: 8 1/4 Hollow Stem Auger SAMPLING METHOD: N/A					SEAL TYPE:	AS - 1/4-inch ber MPE - 3/8-inch B		se pellets
OBSERVER	₹:	Susan Swee	t		SETTING:		7.5 fbg - 5.0 fbg	
REFERENC	CE POINT (R	RP)	West of Termina	l Building	BACKFILL TY	PE: Sand		
ELEVATIO	N OF RP:	Grade			STATIC WATE	R LEVEL:	N/A	
STICK-UP: 1.0 foot below grade SURFACE COMPLETION: Asphalt cover until completed REMARKS:				DEVELOPMEN DURATION:	т метнор:	N/A YIELD:		
ABBREVIAT	TONS: REC=RECOV	MC=MACRO	O CORE W=WA		NGS G=GRA	AB ST=SF FBG=FEET BELC	HELBY TUBE	
DEPTI FROM	H (Feet)	SAMPLE TYPE	RECOVERED (Feet)	PID READING (ppm)		DESCR	IPTION	
1	'	-	1	1	Open bore hole.	DESCRI	IPTION	
FROM	то	-	1	1	Open bore hole.	DESCRI		
FROM 0	TO 5	ТУРЕ	1	1	Open bore hole. CLAY; dark gray; s		n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	
0 5	5 12	С	1	1	Open bore hole. CLAY; dark gray; s	soft; strong petroleum	n odor.	