


1 LOCATION OF WATER WELL: County: Wyandotte Fraction: SE 1/4 NE 1/4 NW 1/4 Section Number: 34 Township Number: T 10 S Range Number: R 25 E/W
 Distance and direction from nearest town or city street address of well if located within city?
103 Funston, Kansas City, KS.

2 WATER WELL OWNER: Carl Privitera Sr.
 RR#, St. Address, Box #: 909 Troost Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Kansas City, Ks. 64106 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 18' ft. ELEVATION:
 Depth(s) Groundwater Encountered: 1 13' ft. 2. . ft. 3. . ft.
 WELL'S STATIC WATER LEVEL: 13.13 ft. below land surface measured on mo/day/yr: 7-29-94
 Pump test data: Well water was . . . ft. after . . . hours pumping . . . gpm
 Est. Yield . . . gpm: Well water was . . . ft. after . . . hours pumping . . . gpm
 Bore Hole Diameter: 8 1/2" in. to 18" ft. and . . . in. to . . . ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes . . . No X . . . If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . . . Clamped . . .
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded . . .
 7 Fiberglass Threaded X
 Blank casing diameter 2.375 in. to 7 1/2" ft. Dia . . . in. to . . . ft. Dia . . . in. to SDR 13 ft.
 Casing height above land surface 2 1/2 in. weight . . . lbs./ft. Wall thickness or gauge No. Sch 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) . . .
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) . . .
 SCREEN-PERFORATED INTERVALS: From 17 1/2' ft. to 7 1/2' ft. From . . . ft. to . . . ft.
 GRAVEL PACK INTERVALS: From 17 1/2' ft. to 6' ft. From . . . ft. to . . . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other . . .
 Grout Intervals: From 6' ft. to 3' ft. From 3' ft. to 0' ft. From . . . ft. to . . . ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? North west How many feet? 70'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.75	Concrete			
.75	8.50	Med olive brn silty clay w/ iron oxides, moist to wet, soft, no odor, slight gray discolorations.			
8.50	12.25	Med olive brn clayey silt, moist to wet, soft, some fine grained sand, no odor.			
12.25	18'	Gray banded silty sand to sandy silt, wet, organics, no odor.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-25-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 8-21-94 under the business name of JB Environmental Drilling by (signature) James Beber