


1 LOCATION OF WATER WELL: County: WYANDOTTE	Fraction SW 1/4 SW 1/4 SW 1/4	Section Number 27	Township Number T 10 S	Range Number R 25 EW
---	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

3126 BRINKERHOFF, KANSAS CITY, KS

2 WATER WELL OWNER: UNISON RR#, St. Address, Box #: 3126 BRINKERHOFF City, State, ZIP Code: KANSAS CITY, KS 66115	MW-B Board of Agriculture, Division of Water Resources Application Number:
--	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 33.7 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 18 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 3-17-97 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.25 in. to 34.0 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <input checked="" type="checkbox"/>
---	--

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 28.2 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No SCHED 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 0.010" 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 12 Other (specify) SCREEN-PERFORATED INTERVALS: From 28.2 ft. to 33.7 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 24.0 ft. to 33.7 ft. From ft. to ft.	CASING JOINTS: Glued Clamped Welded Threaded <input checked="" type="checkbox"/>
--	--

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other CONCRETE Grout Intervals: From 0.0 ft. to 0.6 ft. From 0.6 ft. to 20.3 ft. From 20.3 ft. to 24.0 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) INDUSTRIAL SITE

Direction from well?		How many feet?	
FROM	TO	LITHOLOGIC LOG	PLUGGING INTERVALS
0.0	5.0	BROWN CLAY (Fill)	
5.0	7.0	DK GRAY SILTY SAND	
7.0	20.0	GRAY CLAY	
20.0	34.0	GRAY FINE SAND	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-17-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 9-22-97 under the business name of TERRACON CONSULTANTS INC by (signature) Clay P. Nye
--