

WATER WELL RECORD

Form WWC-5

Division of Water Resources, App. No.

MW-24


1 LOCATION OF WATER WELL: Fraction SW, Section Number 27, Township Number T 10 S, Range Number R 25 W

Distance and direction from nearest town or city street address of well if located within city? 200 FUNSTON RD, KANSAS CITY, KANSAS

Global Positioning Systems (decimal degrees, min. of 4 digits): Latitude, Longitude, Elevation, Datum, Data Collection Method

2 WATER WELL OWNER: HB FULLER, RR#, St. Address, Box # 1200 WILLOW LAKE BLVD, City, State, ZIP Code ST. PAUL, MN 55110

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL 30 ft. Depths Groundwater Encountered (1) 25 ft, (2) 22.93 ft. WELL'S STATIC WATER LEVEL 22.93 ft. below land surface measured on mo day yr 5/15/06

5 TYPE OF CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below)

Blank casing diameter 2 in. to 20 ft. Diameter, Casing height above land surface 0 in., Weight, Wall thickness or gauge No. Schedule 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RM (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw Cut, 9 Drilled holes, 10 Other (specify) No. 10, 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 20 ft to 30 ft. GRAVEL PACK INTERVALS: From 18 ft to 30 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 0 ft to 18 ft.

What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer Storage, 13 Insecticide Storage, 14 Abandoned water well below N/A, 15 Oil well gas well, 16 Other (specify)

Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

Table with columns for FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-9.5 BROWN SLIGHTLY MOIST TO MOIST SLIGHTLY STIFF TO STIFF CLAY; 9.5-20 TAN SLIGHTLY MOIST LOOSE FINE-GRAINED SAND; 20-25 NO RECOVERY; 25-30 RED-BROWN WET, LOOSE FINE-TO-COARSE-GRAINED SAND.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo day year) 709. This Water Well Record was completed on (mo day year) under the business name of MAXS by (signature) David Hunk

INSTRUCTIONS Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send two copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., State 420, Topeka, Kansas 66612-1267. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/geo/waterwells