


1 LOCATION OF WATER WELL: County: Wyandotte	Fraction: SE 1/4 SW 1/4 NE 1/4	Section Number: 34	Township Number: T 10 S	Range Number: R 25 E/W
---	---------------------------------------	---------------------------	--------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?
~220' N of Donovan & 460' E of Conway Trucking, KC

2 WATER WELL OWNER: Huhtamaki Americas RR#, St. Address, Box # : 9201 Packaging Drive City, State, ZIP Code : DeSoto, KS 66018	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 45 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL
	Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 45 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No ✓ ; If yes, mo/day/yr sample was submitted Water Well Disinfectea? Yes No ✓

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped	Welded
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Threaded. ✓ 2 PVC 4 ABS 7 Fiberglass	Blank casing diameter 2 in. to 35 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface -3 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40	
TYPE OF SCREEN OR PERFORATION MATERIAL	7 PVC 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)		
SCREEN-PERFORATED INTERVALS:	From 35 ft. to 45 ft., From ft. to ft.	
GRAVEL PACK INTERVALS:	From 32 ft. to 45 ft., From ft. to ft.	

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete	Grout Intervals: From 0 ft. to 1 ft., From 1 ft. to 32 ft., From ft. to ft.	What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard	10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage	
Direction from well?	How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	24	Asphalt, gravel fill, rubber,			
24	45	Sand (m), Dark Grayish Brown			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/26/2007 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 10/13/07 under the business name of GeoCore, Inc. by (signature) <i>Debra Holt</i>	MW0261, Flushmount Project Name: BM - Mile Marker #1 GeoCore # 1040, #
--	---