

WATER WELL RECORD

Form WWC-5

Division of Water Resources, App. No.

1 LOCATION OF WATER WELL: County: Wyandotte Fraction SE 1/4 SW 1/4 NE 1/4 Section Number 28 Township Number T 100 Range Number R 25 EW

Distance and direction from nearest town or city street address of well if located within city? see attach map Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: N 39 deg 9' 42" Longitude: W 97 deg 37' 44.98" Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: Cham Bennett RR#, St. Address, Box # 900 KIndtepuer Rd City, State, ZIP Code : KCS 66015

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N W E S

4 DEPTH OF COMPLETED WELL: 30 ft. MW-4R Depth(s) Groundwater Encountered (1) 25 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL: 25 ft. below land surface measured on mo/day/yr 11-29-07 Pump test data: Well water was ft. after hours pumping gpm Est. Yield: gpm Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yrs Sample was submitted: Water well disinfected? Yes No X

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass CASING JOINTS: Glued Clamped Welded Threaded X

Blank casing diameter 2 in to 20 ft., Diameter. in. to ft., Diameter in. to ft. Casing height above land surface 1.45 ft. in., Weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass PVC 9 ABS 11 Other (Specify) Sch 40 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 30 ft. to 20 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 30 ft. to 18 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 18 ft. to 15.6 ft., From 15.6 ft. to 1 ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well Direction from well? How many feet?

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Data: 0-18 Brn Clay, 18-30 Yel Brn Clay

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-9-08 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 70438 This Water Well Record was completed on (mo/day/year) 6-9-08 under the business name of MAXS by (signature) David Hansen

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.