WATE	R WE	LL RECORD	Form W	WC-5	Г	Division of Wate	r Resources App. No	AS-108	
		N OF WATER WELL:	Fraction			tion Number		Range Number	
		andotte	SW 1/4 SW 1/4 SV	V 1/4	/4	27	T 10 S	R 25	
	Street/Rural Address of Well Location; if unknown, distance & direction						Global Positioning System (GPS) information:		
fron	from nearest town or intersection: If at owner's address, check here \square .						Latitude: .39.1452 (in decimal degrees)		
312	3126 Brinkerhoff Road Kansas City, KS 66115						Longitude: 94.6210 (in decimal degrees)		
						Elevation:			
2 WATER WELL OWNER: Dow Chemical Corporation						Collection Method:			
RR#, Street Address, Box #: P.O. Box 8361 Kanawha Turnpike						GPS unit (Make/Model: Garmin GPS 12			
City, State, ZIP Code : South Charleston, WV 25303						☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
<u>Est. Accuracy</u> :									
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL V. 22.0' ft.									
1									
	SECTION BOX: Depth(s) Groundwater Encountered (1)								
	Pump test data: Well water wasft. after hours pumping gpm								
EST. YIELDgpm. Well water wasft. after hours pumpinggpm									
W Bore Hole Diameter .3.25" in to .22.0' ft., and in to									
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)									
Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well Air Sparge Well									
 	Was a chemical/bacteriological sample submitted to Department? Yes No								
	S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? ☐ Yes ☑ No									
5 TYPE OF CASING USED: Steel V PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter1" in. to .21.0' ft., Diameter in. to ft., Diameter in. to ft.									
Casing diameter1" in. to .21.0'									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous slot									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)									
SCREEN-PERFORATED INTERVALS: From 21.0 ft. to 22.0 ft., From ft. to									
CDAVEL DACK INTERVALS. From 20.0' A to 22.0' A From									
From									
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From									
Grout In	ntervals:	From	.18.0' ft., Fron	1	. ft. to	ft.,	From	ft. toft.	
What is	the near	est source of possible conta	mination:						
Septic tank								r (specify below)	
	Sewer li	nes		☐ Fuel stora ☐ Fertilizer		☐ Abandoned ☐ Oil well/gas		ir Sparge Point	
		m well							
FROM	TO	LITHOLOG		FROM	ТО			GGING INTERVALS	
0	17.0'	Clay/Silt							
17.0'	22.0'	Sand							
	22.0'	Bottom of Well				<u> </u>			
						<u> </u>			
	ļ								
	ļ			ļ					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year) .6/12/09 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No606 This Water Well Record was completed on (mo/day/year) .8-3-09									
under the business name ofPSA Environmental by (signature)									
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.									
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html.									
KSA 82a-1212 Check: White Copy, Deluc Copy, Pink Copy									