WATER WELL RECORD MW- 26 Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: Fraction	Section Number Township No. Range Number T 10 S R 25 7 E TW
County: Wyandotte 1/4 NW 1/4 2 1/4 NE 1/4 Street/Rural Address of Well Location; if unknown, distance & direction	Z T 10 S R 25 ZE W Global Positioning System (GPS) information:
from nearest town or intersection: If at owner's address, check here	Latitude:39
Kansas City BPU Quindaro Power Station, 3601 N. 12th St.	Longitude: 94.643.7.6 (in decimal degrees)
Kansas City BPO Quindaro Power Station, 360 FN. 12th St. Kansas City, KS	Elevation: 650
	<u>Datum</u> : ☐ WGS 84, ☑ NAD 83, ☐ NAD 27
2 WATER WELL OWNER: Magellan Pipeline Company, L.P	Collection Method:
RR#, Street Address, Box #: P.O. Box 22186 City, State, ZIP Code : Tulsa OK 74121	☐ GPS unit (Make/Model: Garmin 60 ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
City, State, ZIP Code : Tulsa, OK 74121	Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m
3 LOCATE WELL	
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL	
	ft. (2) ft. (3) ft.
N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr	
Pump test data: Well water was	
EST. YIELDgpm. Well water wasft. afterhours pumpinggpm Bore Hole Diameter 8.25	
W	
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)	
SW SE	
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No	
S If yes, mo/day/yr sample was submitted	
mile Water well disinfected? ☐ Yes ☐ No	
5 TYPE OF CASING USED: Steel PVC Other	
CASING JOINTS: Glued Clamped Welded Threaded	
Casing diameter .2.0 in. to3.0 ft., Diameter in. to ft., Diameter ft.	
Casing height above land surface. Flush in., Weight	
TYPE OF SCREEN OR PERFORATION MATERIAL:	
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)	
SCREEN OR PERFORATION OPENINGS ARE:	
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)	
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)	
SCREEN-PERFORATED INTERVALS: From ft. to ft. to ft.	
From	
From - ft to	ft., From ft. to ft.
6 GROUT MATERIALS Neat cement Cement grout Bentonite Other	
Grout Intervals: From 2.3 ft to 2.6 ft, From 2.6 ft to 2. ft, From ft to ft to ft.	
What is the nearest source of possible contamination:	_
Septic tank Lateral lines Pit privy Livestock p	
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer sto	
	rom well
FROM TO LITHOLOGIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
O // Silty Clay, Dark Brown	
// 45 Sand, Fine to Medium Grain	
T CONTRACTORIC OR I ANDONINERIO CERTIFICATION. TIL	well was 🗸 constructed 🗆turing definition
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This wate under my jurisdiction and was completed on (mo/day/year) . 5.1.15.110 an	t well was vi constructed, i reconstructed, or i plugged d this record is true to the best of my knowledge and belief
Kansas Water Well Contractor's License No7.19 This Water Well Re	ecord was completed on (mo/day/@ear) 6/9/10
under the business name of Below Ground Surface, Inc.	by (signature)
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the forect answers. Send three copies	
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at	
http://www.kdheks.gov/waterwell/index.html	
KSA 82a-1212	Check: White Copy, Blue Copy, Pink Copy