USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215 T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health (Water Well Contractors) Forbes-Bldg. 740 Topeka, Kansas 66620

		CB A			Forbes-Bldg. 740
		· · ·	10 5	NWS	Topeka, Kansas 66620
County	Township name	Fraction S. W.	4 Section	on number	Town number
1 Location of well:		N.F.Y	4]	28	105. SW.
Distance and direction from nearest town or ci	HIN K.C. K	-5. 3 % of	vner of well	: GA	PHEY CONST. CO.
Street address of well location if in city: B.	PU - QUA	JEARN.		13	
Street address of well location if in city:	DIST	ZICIT A	ddress:	K	, c, Mo,
ocate with "X" in section below:	Sketch map:			•	4 Well depth: 8911 ft. Date of completion 316
N	. 0	WER			Well diameter 42_ in.
	Mo. R	.141			5 Cable tool Rotary Driven Dug
iii					Hollow rod Jetted Bored Reverse rotary
w ! E	✓ d)□	14/5			6 Use: Domestic Public supply Industry
w t	~ \ \\	.11))			☐ Irrigation ☐ Air conditioning ☐ Commercial ☐ Test well ※ DEWATER LNG
		* 1†((7 Casing: Material SEE Height: above/below
	\sim	<u> </u>			Threaded Welded Surface 21 in.
S		X 1711 -			Diam. Weight 29.3 lbs./ft
1 Mile		X	<u> </u>		12 in. to 191 ft. depth Drive shoe? Yes No
WELL No. 2 Typ	e and color of material		From	То	in. to ft. depth!
WELL NO. Z			+		8 Screen: Manufacturer DOERR
FILL			0	2'	Type SLOTTED Dia. 12"
parell Chila	C. A.		21	001	Slot/gauze 76A. Length 401
BROWN SANDY (LAY		12	221	Set between 49.1 ft. and 89.1 ft
VERY FINE SAN	D		221	82'	Fittings: Gravel pack XYes No Size range of material 4
	-	C - 1 - 1			9 Static water level
MEDIUM TO COARS	e SAND F	GRAVEL	82	87.4	215 ft. below land surface Date 3/17/76
TRACE OF FINE	SAND				Pumping level below land surfaces:
17702 01 1132					55 ft. after 168 hrs. pumping 350g.p.m.
					ft. after hrs. pumping g.p.m. Estimated maximum yield g.p.m.
					11 Water sample submitted:
	A	****	_		Yes No Date
					12 Well head completion:
					Pitless adapter X Inches above grade
****					13 Well grouted? Yes No NATURAL
				Ì	□ Neat cement □ Bentonite □ BACKFILL Depth: From □ ft. to 69.1 ft.
					CAAL
		· · · · · · · · · · · · · · · · · · ·	_	ļ	14 Nearest source of possible contamination: FILE ft. Do Direction WEST Type
					Well disinfected upon completion? Yes No
					15 Pump: X Not installed
				ļ	Manufacturer's name HP Volts
					Length of drop pipe ft. capacity g.m.p.
					Туре:
					Submersible Turbine
live	e a second sheet if needed)				☐ Jet ☐ Reciprocating ☐ Certrifugal ☐ Other
16 Remarks: elevation APPRox. 800- 75 16 mm					17 Water well contractor's certification:
TO Kellidiks: elevation ATTKOX.	000 12 18 16 16 16 16 16 16 16 16 16 16 16 16 16				This well was drilled under my jurisdiction and this
					report is true to the best of my knowledge and belief.
Topography:					LAYNE-WESTERN Co. 149
☐ Hill ☐ Slope					Business name Address Of W. 29 THY K. C. Mo.
Upland					Signed Date 10/7/2
V Velley					Authorized representative