


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 27 Township Number T 10 S Range Number R 25 E
 County: WYANDOTTE

Distance and direction from nearest town or city street address of well if located within city?

3126 BRINKERHOFF, K.C. KS 66115 Well # MW 12B

2 WATER WELL OWNER: UNISON TRANSFORMER SERVICE
 RR#, St. Address, Box # : 3126 BRINKERHOFF ROAD Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : KANSAS CITY, KANSAS 66115 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 49 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 16.9 ft. below land surface measured on mo/day/yr 5/5/94
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 8 in. to 5.4 in. to in. to in.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes. No. X If yes, mo/day/yr sample was sub-
 mitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded. X
 Blank casing diameter 2 in. to 3.9 in. Dia in. to in. Dia in. to in.
 Casing height above land surface 72 in., weight 0.70 lbs./ft. Wall thickness or gauge No. SCHD 40
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 10-SLOT 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 3.9 ft. to 4.9 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 3.6 ft. to 4.9 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 1.5 ft., From 1.5 ft. to 3.6 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
3 13 Insecticide storage CLOSED INDUSTRIAL FACILITY
 Direction from well? WEST How many feet? 80 FT

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.5	FILL			
1.5	5	LT BRN LOW PLASTIC CLAYEY SILT (ML)			
5	6.5	MIXED LOW PLASTIC SILTY CLAY & CLAYEY SILT (ML-CL)			
6.5	8	LOW PLASTIC SILTY CLAY (CL)			
8	15	LOW PLASTIC CLAYEY SILT (ML)			
15	17	LT BRN V FINE SILTY SAND (SM)			
17	20	V FINE SILTY SAND w/ SILT LAYERS (SM w/ML)			
20	22.5	LOW PLASTIC SILT (ML)			
22.5	29	SANDY SILT TO V FINE SILTY SAND (SM)			
29	41	FINE SAND w/ V FINE SILTY SAND (SP w/SM)			
41	53	MED SAND, POORLY GRADED w/ TR COARSE SAND & FINE GVL (SP)			
53	54	FINE TO MED SAND w/ SOME LAYERS OF SILTY SAND w/ TR. CLAY (SP w/SM)			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) MAY 4, 1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. AD057102 This Water Well Record was completed on (mo/day/yr) JULY 13, 1994 under the business name of _____ by (signature) [Signature]