

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: CLAY Fraction: NW 1/4 NW 1/4 SW 1/4 Section Number: 30 Township Number: T 10 S Range Number: R 4 E

Distance and direction from nearest town or city street address of well if located within city?

1760 5TH Rd

2 WATER WELL OWNER: Jeremy & Joan Lebo
 RR#, St. Address, Box #: 1760 5TH Rd Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: WAKEFIELD, KS 67487 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 120 ft. ELEVATION: —
 Depth(s) Groundwater Encountered 1. 77 ft. 2. — ft. 3. — ft.
 WELL'S STATIC WATER LEVEL: 72 ft. below land surface measured on mo/day/yr 4/27/98
 Pump test data: Well water was — ft. after — hours pumping — gpm
 Est. Yield: 8 gpm; Well water was — ft. after — hours pumping — gpm
 Bore Hole Diameter: 8 5/8 in. to 120 ft., and — in. to — ft.
 WELL WATER TO BE USED AS:
 Domestic Feedlot Oil field water supply Dewatering Other (Specify below)
 Irrigation Industrial Lawn and garden only Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes — No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No —

5 TYPE OF BLANK CASING USED:
 Steel RMP (SR) Asbestos-Cement Other (specify below) Concrete tile CASING JOINTS: Glued X Clamped —
 PVC ABS Fiberglass Threaded —
 Blank casing diameter: 5" in. to 100 ft., Dia — in. to — ft., Dia — in. to — ft.
 Casing height above land surface: 18 in., weight — lbs./ft. Wall thickness or gauge No. SDR 26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel Stainless steel Fiberglass RMP (SR) Other (specify) 7 PVC Asbestos-cement
 Brass Galvanized steel Concrete tile ABS None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 Continuous slot Mill slot Wire wrapped Drilled holes
 Louvered shutter Key punched Torch cut Other (specify) —
 SCREEN-PERFORATED INTERVALS: From 100 ft. to 120 ft., From — ft. to — ft.
 SAND GRAVEL PACK INTERVALS: From 25 ft. to 120 ft., From — ft. to — ft.

6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other —
 Grout Intervals: 3 From 3 ft. to 25 ft., From — ft. to — ft.
 What is the nearest source of possible contamination:
 Septic tank Lateral lines Pit privy Livestock pens Abandoned water well
 Sewer lines Cess pool Sewage lagoon Fuel storage Oil well/Gas well
 Watertight sewer lines Seepage pit Feedyard Fertilizer storage Other (specify below)
 13 Insecticide storage
 Direction from well? NORTH DOWNGRADIENT How many feet? 300 FEET

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Gravelly soil, brn			
4	17	Limestone, TAN			
17	20	shale, grey			
20	21	Limestone, TAN			
21	25	shale, Tan			
25	36	shale, grey			
36	70	shale, brn			
70	81	Limestone, Tan			
81	95	shale, grey			
95	111	Limestone, Tan to grey			
111	120	shale, grey			
120	TD	end of bore hole			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 4/27/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 4/27/98 under the business name of ACI by (signature) [Signature]