

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>GARY</u>		<u>SW 1/4 SW 1/4 SE 1/4</u>	<u>18</u>	T <u>10</u> (S)	R <u>5</u> (E)
Distance and direction from nearest town or city street address of well if located within city? <u>by City Building 20' North of Water Tower</u>					
2 WATER WELL OWNER: <u>CITY OF MILFORD</u>					
RR#, St. Address, Box #: <u>CITY BUILDING</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: <u>MILFORD, KS</u>			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>was 120</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered <u>was 40</u> ft. 1. <u>40</u> ft. 2. <u>40</u> ft. 3. <u>40</u> ft.			
		WELL'S STATIC WATER LEVEL <u>was 70</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was <u>was 30</u> gpm; Well water was <u>was 30</u> ft. after <u>was 30</u> hours pumping			
		Bore Hole Diameter: <u>?</u> in. to <u>?</u> ft., and <u>?</u> in. to <u>?</u> ft.			
		WELL WATER TO BE USED AS: <u>was 8</u> Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? <u>Yes</u> No			
5 TYPE OF BLANK CASING USED:					
1 Steel <u>was 2</u> PVC		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
Blank casing diameter <u>6</u> in. to <u>100</u> ft. Dia		17 Fiberglass		8 Concrete tile	
Casing height above land surface <u>CUT OFF 3' below Ground</u> lbs./ft. Wall thickness or gauge No.				9 Other (specify below)	
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		6 Concrete tile	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut	
1 Continuous slot		6 Wire wrapped		9 Drilled holes	
2 Louvered shutter		7 Torch cut		10 Other (specify) <u>NONE</u>	
3 Mill slot		8 RMP (SR)		11 None (open hole)	
4 Key punched		9 ABS		12 None used (open hole)	
SCREEN-PERFORATED INTERVALS: From <u>70</u> ft. to <u>120</u> ft., From <u>70</u> ft. to <u>120</u> ft., From <u>70</u> ft. to <u>120</u> ft., From <u>70</u> ft. to <u>120</u> ft.					
GRAVEL PACK INTERVALS: From <u>70</u> ft. to <u>120</u> ft., From <u>70</u> ft. to <u>120</u> ft., From <u>70</u> ft. to <u>120</u> ft., From <u>70</u> ft. to <u>120</u> ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
4 Other					
Grout intervals: From <u>3</u> ft. to <u>70</u> ft., From <u>3</u> ft. to <u>70</u> ft., From <u>3</u> ft. to <u>70</u> ft., From <u>3</u> ft. to <u>70</u> ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below) <u>NONE</u>	
Direction from well? <u>NONE CLOSE</u>					
How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Compacted Clay			
3	40	Bentonite Grout			
40	120	Clorinated Gravel			
<div style="font-size: 2em; transform: rotate(-45deg); opacity: 0.5;">Plugged</div>					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6/16/93</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>451</u> This Water Well Record was completed on (mo/day/yr) <u>6/25/93</u> under the business name of <u>Waldman Well Drilling</u> by (signature) <u>Waldman</u> CWO/PT					