

1 LOCATION OF WATER WELL: County: GEARY Fraction: SE 1/4 SE 1/4 SE 1/4 Section Number: 20 Township Number: T 10 S Range Number: R 5 E
 Distance and direction from nearest town or city street address of well if located within city? MILFORD LAKE MW 2

2 WATER WELL OWNER: US ARMY
 RR#, St. Address, Box #: DEH FT RILEY KS 66442 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: DEH FT RILEY KS 66442 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	<div style="border: 1px solid black; width: 100px; height: 100px; position: relative;"> <div style="position: absolute; top: 50%; left: 50%; transform: translate(-50%, -50%);">X</div> </div>	<div style="border: 1px solid black; width: 100px; height: 100px; position: relative;"> <div style="position: absolute; top: 50%; left: 50%; transform: translate(-50%, -50%);">X</div> </div>	E
S			

4 DEPTH OF COMPLETED WELL: 47 ft. ELEVATION: 999 ft.
 Depth(s) Groundwater Encountered: 1. 999 ft. 2. 47 ft. 3. 47 ft.
 WELL'S STATIC WATER LEVEL: 999 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 47 ft. after 47 hours pumping 47 gpm
 Est. Yield: 47 gpm: Well water was 47 ft. after 47 hours pumping 47 gpm
 Bore Hole Diameter: 6 in. to 47 ft., and 47 in. to 47 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted No
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded
 Blank casing diameter: 6 in. to 37 ft., Dia. 37 in. to 47 ft., Dia. 47 in. to 47 ft.
 Casing height above land surface: 30 in., weight 30 lbs./ft. Wall thickness or gauge No. 30
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) 47
 SCREEN-PERFORATED INTERVALS: From 37 ft. to 47 ft., From 47 ft. to 47 ft., From 47 ft. to 47 ft.
 GRAVEL PACK INTERVALS: From 37 ft. to 47 ft., From 47 ft. to 47 ft., From 47 ft. to 47 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other TRAINING AREA
 Grout Intervals: From 0 ft. to 37 ft., From 37 ft. to 47 ft., From 47 ft. to 47 ft., From 47 ft. to 47 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Direction from well? W, N How many feet? W, N

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>TD</u>	<u>SILTY CLAY + SHALE</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/24/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. SP1 This Water Well Record was completed on (mo/day/yr) 8/24/94 under the business name of LAYNE INC by (signature) [Signature]