

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

1 LOCATION OF WATER WELL: County: Riley Co. Fraction SE 1/4 SE 1/4 SE 1/4 1/4 Section Number 33 Township No. T 10 S Range Number R 8 E W Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: Ft Riley Range Global Positioning System (GPS) information: Latitude: Longitude: Elevation: Datum: Collection Method: Est. Accuracy:

2 WATER WELL OWNER: Ft. Riley RR#, Street Address, Box #: Ft. Riley, KS City, State, ZIP Code: 3 LOCATE WELL WITH AN "X" IN SECTION BOX: N W E S 4 DEPTH OF COMPLETED WELL 120' Depth(s) Groundwater Encountered (1) 65 (2) 60 (3) 60 WELL'S STATIC WATER LEVEL 60 Pump test data: Well water was EST. YIELD 16 gpm. Bore Hole Diameter 9" in. to 120' ft. WELL WATER TO BE USED AS: Public water supply Domestic Feedlot Oil field water supply Dewatering Other Irrigation Industrial Domestic-lawn & garden Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted. Water well disinfected? Yes No

5 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 5 in. to 10.0 ft., Diameter in. to Casing height above land surface 2.1 in., Weight 5.4 lbs./ft., Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other Brass Galvanized Steel None used SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None Louvered shutter Key punched Wire wrapped Saw cut Other SCREEN-PERFORATED INTERVALS: From 10.0 ft. to 120 ft. GRAVEL PACK INTERVALS: From ft. to ft.

6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 5 ft. to 30 ft. What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well Direction from well Distance from well

Table with 6 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows include: 0-1 Top Soil, 1-12 Brown Clay, 12-16 Limestone, 16-41 Gray Shale, 41-44 Limestone, 44-65 Brown Shale, 65-70 Limestone (WATON), 70-83 Brown Shale, 83-109 Limestone, 109-120 Gray Shale (DARK)

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 9/29/2010 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 45 This Water Well Record was completed on (mo/day/year) 10/19/2010 under the business name of Halderman, W.K., P.C. by (signature) Gary J. ...

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.