١				
I				
1	9	=	2	
Ì		İ	i	
ŀ	Š	-	2	
	ì			
ı	ç	7	2	
	Ċ		)	
ı	3	Ž	•	
ı	•	۲.		

	WATER WELL RECORD FO		(SA 82a-1212		D
1 LOCATION OF WATER WELL:	Fraction  NE 1/4 SE 1/4 SE		Number T	Township Number 10 s	Range Number R <b>7E</b> w
County: Riley Distance and direction from nearest tov	vn or city street address of well if located w			.,	
	KSU Landfill, Ma	nhattan, Kan	sas		
	s State University Attn: Kelly	Phillips			
RR#, St. Address, Box # : 108 Ed	Iwards Hall				sion of Water Resources
City, State, ZIP Code : Manha	ttan, KS 66505		A <sub>I</sub>	pplication Number:	
3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL Depth(s) Groundwater Encountered 11.5	31	ft. ELEVATIO	N:	3 Ft. S
	WELL'S STATIC WATER LEVEL	12.5 ft. bel	ow land surface	measured on mo/day/	yr <b>07/31/08</b>   7
	Pump test data: Well water				umping Gpm c
M N E	Est. Yield Gpm: Well water Bore Hole Diameter 8.625 In. to WELL WATER TO BE USED AS: 5 P 1 Domestic 3 Feed lot 6 O	was 36 ublic water supp il field water sup	Ft. afte ft. an oply 9	d Hours p d in Air conditioning 1 Dewatering 1	oumping Gpm 7 to Ft. 5 I Injection well 2 Other (Specify below)
swse	2 Irrigation 4 Industrial 7 La				
	Was a chemical/bacteriological sample s	and the second s	The second secon	No A If yes, all Disinfected? Yes	
5 TYPE OF BLANK CASING USED:	5 Wrought Iron			ASING JOINTS: Glue	
	(SR) 6 Asbestos-Cement				
2 PVC 4 ABS	7 Fiberglass		30, 20.0,	Barrier Branch and Branch	aded X
Blank casing diameter 2	in to 21 Dia	In. to			in. toft.
Casing height above land surface	FLUSH In., weight S	CH 40	Lbs./ft. Wall	thickness or gauge No	
TYPE OF SCREEN OR PERFORATION				10 Asbestos-ceme	
	ess steel 5 Fiberglass	8 RN	MP (SR)	11 Other (specify)	- Later
2 Brass 4 Galva SCREEN OR PERFORATION OPENII	inized steel 6 Concrete tile	9 At ed wrapped	8 8	12 None used (ope	11 None (open hole)
		wrapped		Orilled holes	Tr None (openhole)
SCREEN-PERFORATED INTERVALS	0.4			ft. t	
SCREEN-FERFORATED INTERVALS					C Et
SAND BACK INTERVALS		31	ft. From		
SAND PACK INTERVALS:	and the second s			ft. t	
6 00017 111 75011					
6 GROUT MATERIAL: 1 Neat	cement 2 Cement grout Ft.	3 Benton Ft.	11te	her	
Grout Intervals From3 0	ft. to 18 From2 1		20	ft. From	ft. toft.
What is the nearest source of possible	contamination:		10 Livestock p	ens 14 Ab	andoned water well
1 Septic tank	4 Lateral lines 7 Pit privy		11 Fuel storag	e 15 <u>Oil</u>	well/ Gas well
2 Sewer lines	5 Cess pool 8 Sewage	lagoon	12 Fertilizer st	orage 16 Oth	ner (specify below)
3 Watertight sewer lines	6 Seepage pit 9 Feedyar	ď	13 Insecticide	storage Co	ntaminated Site
Direction from well?			low many feet?		
FROM TO CODE	LITHOLOGIC LOG	FROM	то	PLUGGING IN	
0 11.5 Fi					
	Ity clay (CL)				
15 22.5 CI	ay trace of sand				
	and with clay and gravel nd of Borehole				
31 10 21	id of Bolellole	-			
		1 :			
	•			7 1	
7 CONTRACTOR'S OR LANDOWNE	R'S CERTIFICATION: This water well wa	s (x) constructed	d. (2) reconstru	cted, or (3) plugged upo	ler my jurisdiction and w
Completed on (mo/day/yr)	07/31/08				lge and belief. Kansas
Water Well Contractor's License No.				•	day/yr) 08/31/08
under the business name of	Associated Environmenta			nature) Bradley J	
INSTRUCTIONS: Please fill in blan	ks and circle the correct answers. Send three	copies to Kansas	Department of He	alth and Environment, By	rea of Water, Topeka,
Kansas 66620-0001. Telephone: 91	13-296-5545. Send one to WATER WELL OW	NER and retain or	ne for your record	Burles 1/0	ho
				177	