: 1	
_	
- }	
	1. 5
٠,	
	٠.
.	
	O
t.	Ť
	\mathbf{T}
	Ω
_	E USE ON
۳.	ĭĞ
	Ж
t.	7
t. n n t.	=
- 1	-≺
	1
÷	10 m
4	
	1.5
	1.0
	1 -
	1.50
7.7	1
	1.
	- 11
	-
	ŀ
ι.	70
t	
t. t.	1
t.	
-	

		L RECORD Form V			
LOCATION OF WATER WELL:	Fraction		Section Numb	The second secon	Range Number
unty: Riley	NE 1/4 SE			т 10 s	R 7E w
stance and direction from nearest too		of well it located within			
WATER WELL OWNER: Kansa		Attn: Kelly P	hillips		
R#, St. Address, Box # : 108 E	dwards Hall	세계 방송 바람이다.		Board of Agriculture, Div	vision of Water Resources
ty, State, ZIP Code : Manha	attan, KS 66505			Application Number:	
LOCATE WELL'S LOCATON WITH		ETED WELL	30 # =	EVATION	
AN "X" IN SECTION BOX:	Deeth of Cower	ETED WELL	, , , , , , , , , , , , , , , , , , ,	_EVATION:	3 Ft.
	Depth(s) Groundwater		5 4 halaw lan	ft. 2 ft. d surface measured on mo/day	07/31/08
N					
				Ft after hours	
NWNE	Describble Dismeter	8 625 In to	30	Ft. after Hours	n to Ft.
	- WELL WATER TO BE	USED AS: 5 Public	water supply	ft. and i	1 Injection well
W	1 Domestic 3 F	eed lot 6 Oil fie	ld water supply	9 Dewatering	2 Other (Specify below)
	2 Irrigation 4 I			estic) 10 Monitoring well	
swtse				nt? Yes No X If yes	
∀	Submitted			Water Well Disinfected? Yes	No X
TYPE OF BLANK CASING USED:				CASING JOINTS: Glue	
		Asbestos-Cement S			
2 PVC 4 ABS		iberglass			aded X
	항공기 없는 아이들의 사람이 없다.	Ft			
•	in. to 20	Dia	in. to	ft., Dia	
Casing height above land surface	FLUSH In , we	eight SC H	140 Lbs	./ft. Wall thickness or gauge No	
YPE OF SCREEN OR PERFORATION	N MATERIAL:		7 PVC	10 Asbestos-cem	
1 Steel 3 Stain	ess steel 5 F	Fiberglass	8 RMP (SF	10 Asbestos-cem 11 Other (specify 12 None used (op 8 Saw cut	
2 Brass 4 Galva	inized steel 6 (Concrete tile	9 ABS	12 None used (or	en hole)
CREEN OR PERFORATION OPENII	NGS ARE:	5 Gauzeo v			11 None (open noie)
1 Continuous slot 3	Mili SiOt	6 Wire wrap 7 Torch cut	pheo	9 Drilled Hotes	
	Key punched			10 Other (specify)	L
SCREEN-PERFORATED INTERVALS		ft. to			to ft.
		ft. to			to Ft.
SAND PACK INTERVALS:		ft. to			to Ft.
	From	ft. to			to Ft.
GROUT MATERIAL: 1 Neat	cement 2 Ceme	ent grout	3 Bentonite	4 Other	
Grout Intervals From3 0	ft to 17 Fr	rom2 17	to	19 ft. From	ft. to ft.
Vhat is the nearest source of possible					pandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy	. 11 Fu	el storage 15 O	l well/ Gas well
2 Sewer lines	5 Cess pool	8 Sewage lage	oon 12 Fe	ertilizer storage 16 O	her (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Ins	secticide storage Co	ontaminated Site
Direction from well?				any feet?	·. '
FROM TO CODE	LITHOLOGIC	LOG	FROM TO	PLUGGING I	NTERVALS
0 2 To	psoil				
	lay, stiff brown				
3 30 Si	ity clay (CL) soft	ellow orang			
30 TD E	nd of Borehole				
	<u> </u>				
7 CONTRACTOR'S OR LANDOWNE		his water well was (x) constructed, (2) re	econstructed, or (3) plugged un	der my jurisdiction and w
Completed on (mo/day/yr)			And this record	is true to the best of my knowle	dge and belief. Kansas
Vater Well Contractor's License No.	58	5	This Water Well	Record was completed on (mo	/day/yr) 08/31/08
under the business name of	Associated E	nvironmental,	nc.	By (signature) Bradley	Johnson
INSTRUCTIONS: Please fill in blan	ks and circle the correct ans	wers. Send three copie	es to Kansas Departr	nent of Health and Environment, B	uleay of Water, Topeka,