10872 20110168 Form WWC-5 WATER WELL RECORD Division of Water Resources App. No. Township No. | Range Number 1 LOCATION OF WATER WELL: Fraction Section Number 1/4 SW 1/4 NW 1/4 NE 1/4 27 T 10 S R 7 ME W Global Positioning System (GPS) information: Street/Rural Address of Well Location; if unknown, distance & direction Latitude: 39.157327 (in decimal degrees)

Longitude: -96.63377 (in decimal degrees) from nearest town or intersection: If at owner's address, check here Approximately 3 miles southwest of Manhattan unknown Elevation: Datum: ☐ WGS 84, ☒ NAD 83, ☐ NAD 27 Collection Method:

GPS unit (Make/Model: WAAS

Digital Map/Photo, Topographic Map, Land Survey
Est. Accuracy: <3 m, 3-5 m, 5-15 m, >15 m 2 WATER WELL OWNER: Wildcat Construction RR#, Street Address, Box #: 4421 W. Harry City, State, ZIP Code : Wichita, KS 67277 3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 41 ft. Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 13.30 ft. below land surface measured on mo/day/yr 07/15/11

Pump test data: Well water was not checked ft. after hours pumping gpm SECTION BOX: --NW--*--NE--W --SW-----SE---☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well Irrigation Was a chemical/bacteriological sample submitted to Department? Yes No S If yes, mo/day/yr sample was submitted |-----1 mile------Waterwell disinfected? Tyes No 5 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Solved Clamped Welded Threaded
Casing diameter 8 in. to 20 ft., Diameter in. to ft., Diameter in. to ft.

Casing height above land surface 12 in., Weight 5.59 lbs./ft., Wall thickness or gauge No. 332 TYPE OF SCREEN OR PERFORATION MATERIAL: Other (Specify) Stainless Steel
Galvanized Steel **▼** PVC Steel None used (open hole) Brass SCREEN OR PERFORATION OPENINGS ARE:

Continuous slot Mill slot Gauze wrapped Saw cut Other (specify)

Louvered shutter Key punched Wire wrapped Saw cut Other (specify)

SCREEN-PERFORATED INTERVALS: From 20 ft. to 40 ft., From ft. to ft.

From ft. to ft., From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 19 ft. to 44 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

From ft. to ft., From ft. to ft.

OGROUT MATERIAL: Neat cement Cement grout Bentonite Other

Grout Intervals: From ft. to ft., From 0 ft. to 19 ft., From ft. to ft.

What is the nearest source of possible contamination:

Septic tank Lateral lines Pit privy Insecticide storage Abandoned water well Other (specify below) None Known Distance from well Direction from well LITHO. LOG (cont.) or PLUGGING INTERVALS LITHOLOGIC LOG FROM FROM TO Note: please see attached letter from Topsoil 0 Richard Harper waiving the 20 ft grout 1 10 Sand, fine requirement for this project. 10 17 Clay, sandy, gray, soft Sand & gravel, fine 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 07/15/11 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/year) 07/26/11 under the business name of Clarke Well & Equipment, Inc. by (signature) under the business name of Clarke Well & Equipment, Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html. Check: White Copy, Blue Copy, Pink Copy KSA 82a-1212

137

14-11