152 10872 20110168 WATER WELL RECORD Form WWC-5 Division of Water Resources App. No. 1 Township No. Range Number Section Number 1 LOCATION OF WATER WELL: Fraction 1/4 NW 1/4 SE 1/4 NW 1/4 27 T 10 S R 7 \boxtimes E \square W County: Global Positioning System (GPS) information: Street/Rural Address of Well Location; if unknown, distance & direction Latitude: 39.155016 (in decimal degrees) from nearest town or intersection: If at owner's address, check here Longitude: -96.637955 (in decimal degrees) Approximately 3 miles southwest of Manhattan 2 WATER WELL OWNER: Wildcat Construction RR#, Street Address, Box #: 4421 W. Harry City, State, ZIP Code : Wichita, KS 67277 3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 41 ft. Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 14.75 ft. below land surface measured on mo/day/yr 07/21/11

Pump test data: Well water was not checked ft. after hours pumping gpm SECTION BOX: Ν EST. YIELD ____gpm. Well water was _____ft. after _____hours pumping ____gpm

Bore Hole Diameter ____12 in. to ____41 ft., and _____in. to _____ft.

WELL WATER TO BE USED AS: ___ Public water supply ____ Geothermal ____ Injection well

_____ Domestic ___ Feedlot ____ Oil field water supply _____ Dewatering ____ Other (Specify below)

_____ Irrigation ____ Industrial ____ Domestic-lawn & garden _____ Monitoring well --NW----NE----SW----SE--Was a chemical/bacteriological sample submitted to Department? Yes No S If yes, mo/day/yr sample was submitted |----- | mile-----| Waterwell disinfected? Tyes No Other 5 TYPE OF CASING USED: Steel **▼** PVC CASING JOINTS: Glued Clamped Welded Threaded

Casing diameter 8 in. to 20 ft., Diameter in. to ft., Diameter in. to ft.

Casing height above land surface 12 in., Weight 5.59 lbs./ft., Wall thickness or gauge No. .332 TYPE OF SCREEN OR PERFORATION MATERIAL: Other (Specify) ▼ PVC Steel Stainless Steel None used (open hole) Galvanized Steel SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Saw cut Other (specify)

Louvered shutter Key punched Wire wrapped Saw cut Other (specify)

SCREEN-PERFORATED INTERVALS: From 20 ft. to 40 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 19 ft. to 41 ft., From ft. to ft.

From ft. to ft., From ft. to ft. 6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other

Grout Intervals: From ft. to ft., From 0 ft. to 19 ft., From ft. to ft.

What is the nearest source of possible contamination: Lateral lines Pit privy Livestock pens Insecticide storage Abandoned water well Seepage pit Feedyard Fertilizer storage Oil well/gas well Other (specify below) Septic tank Sewer lines None Known Watertight sewer lines Seepage pit Feedyard Distance from well Direction from well LITHO. LOG (cont.) or PLUGGING INTERVALS LITHOLOGIC LOG FROM FROM TO Note: please see attached letter from Topsoil 0 Richard Harper waiving the 20 ft grout 13 5 Clay, sandy requirement for this project. 13 Sand & gravel, fine 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 07/21/11 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/year) 07/26/11 under the business name of Clarke Well & Equipment, Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-55522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html. Check: White Copy, Blue Copy, Pink Copy KSA 82a-1212

29-11