Seg.		WATE	R WELL RECORE	D Form W	WC-5	KSA 82a-12	212		
LOCATION OF WAT	ER WELL:	Fraction			Section	on Number	Township Numbe	er Ra	ange Number
ountv:	Riley	SW 1/4	NE 1/4	SW 1/4	<u> </u>	18	т 10	s R	8 E
stance and direction f	rom nearest to	wn or city street add	dress of well if loo	cated within	city?	. 1/0			
T			1630 Poyntz	z Ave. Ma	nnattar	1, KS			
WATER WELL OWN	ER: Clay's	Automotive	Service					District of	Matau Danasaa
- R#, St. Address, Box i	‡ : 1630 I	oyntz Ave.	00				Board of Agricultur		water Resources
ity, State, ZIP Code	: Manh	attan, KS 6650	02				Application Number	<u>:r:</u>	
LOCATE WELL'S LO AN "X" IN SECTION	BOX.	1 4 DEPTH OF C	OMPLETED WE	LL	30	ft. ELEV	ATION:	1042.2	.8
N				ed 1.5	24	ft.	2	ft. 3	Ft.
4		WELL'S STATIC	WATER LEVEL	23.50	) ft b	elow land si	urface measured on m	o/dav/vr	07/03/14
1 1	i i	WELL S STATIO	toot data: \\/a	ll water was	11. 12	Elow land of	after h	iours numping	a Gpm
NW	NE	Fump	) lesi data. Wei	ll water was		' '	i. after }	fours numning	d Gpm
E W		Est. Yield	Spin: wei	ii watei was	30	' '	ft and	in to	Ft Ft
-	l	WELL WATER T	O RE USED AS:	n. to 5 Public	water sur	oply	ft. and 8 Air conditioning 9 Dewatering	11 Injec	tion well
s\X	SÈ	1 Domestic	3 Feed lot	6 Oil field	l water si	upply	9 Dewatering	12 Othe	er (Specify below)
		2 Irrigation	4 Industrial	7 Lawn a	nd garde	en (domestic	) 10 Monitoring we	1	MW-3
7		Was a chemical/	hacteriological sa	ample submi	tted to De	epartment?	Yes No X	If yes, mo/da	y/yr sample was
S	_	Submitted	baotonological co	impro ouzim			er Well Disinfected?		
TYPE OF BLANK C.	ASING LISED:		5 Wrought Iro	n 8	Concret		CASING JOINTS:		
			6 Asbestos-C					Welded	
1 Steel	THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAM	(ON)			•			Threaded	Х
2 PVC	4 ABS		7 Fiberglass Ft.,					A THE RESIDENCE OF THE PARTY OF	
lank casing diameter	2	in. to 20	Dia		In. to	)	ft., Dia	in. to	ft.
asing height above la	nd surface	FLUSH	In., weight	SCH	40	Lbs./ft.	Wall thickness or gau	ige No.	
YPE OF SCREEN OF			,		7 F	PVC	10 Asbestos	s-cement	
1 Steel			5 Fiberglass		Boom	RMP (SR)			
2 Brass	4 Galva	less steel anized steel	6 Concrete til	le	9 A	ABS	12 None us	ed (open hole	e)
CREEN OR PERFOR				Gauzed wr	apped		8 Saw cut	11 N	one (open hole)
1 Continuous slo		Mill slot		Wire wrapp	oed		9 Drilled holes		
2 Louvered shut	ter 4	Key punched		Torch cut			10 Other (specify)		
CREEN-PERFORATE	ED INTERVALS	S: From	<b>20</b> ft. to	)	30	ft. F	rom	ft. to ,	ft.
		From	ft. to	)		ft. F	rom	ft. to	
SAND PACK IN	NTERVALS:	From	<b>18</b> ft. to	)	30	ft. F	rom	ft. to	
		From		)		ft. F			<u>Ft.</u>
GROUT MATERIAL	: 1 Neat	cement 2	Cement grout		3 Bento	onite	4 Other		
			Ft.		Ft.				
rout Intervals From				16	to	18	ft. From	#t. t	to tt.
/hat is the nearest sou	irce of possible						tock pens		
<ol> <li>Septic tank</li> </ol>		4 Lateral lines		it privy		11 Fuels	ŭ	15 Oil well/ G	
2 Sewer lines		5 Cess pool		ewage lago	on			16 Other (spe	THE RESIDENCE OF THE PROPERTY OF THE PARTY O
3 Watertight sew	er lines	6 Seepage pit	9 F	eedyard			ticide storage	Contam	ninated Site
irection from well?						How many			
FROM TO	CODE		OGIC LOG		FROM	ТО	PLUGO	SING INTERV	ALS
0 0.5		sphalt (~6")					- Annual Lander, - Annu		and the second s
0.5 30		ilty Clay	T						
30 TD	E	nd of Boreho	ie						
						<del>  </del>			
	_								
CONTRACTOR'S	OR LANDOWN	ER'S CERTIFICAT	ION: This water	well was (x)	construc	ited, (2) reco	onstructed, or (3) plug	ged under my	jurisdiction and w
					. And thi	is record is t	rue to the best of my l	nowledge an	id belief. Kansas
/ater Well Contractor			585		This W	ater Well Re	ecord was completed	on (mo/day/yr	r) 07/23/14
ndar the business na	na of	Associa	ted Environi	mental, i	nc.	E	By (signature) Brad	iey J. Joh	nson
INSTRUCTIONS:.	Please fill in bla	nks and circle the cor	rect answers. Sen	d three copie	s to Kansa	as Departmer	nt of Health and Environ	nent, Bureau o	orvvater, Lopeka,
Kansas 66620-000	ı. reiephone: 9	13-296-5545. Send	ONE IO WATER WE	LLL OVVINER	and retail	TOTHE TOT YOUR	1000103.		<i>H - 11</i>