		WATE	R WELL RECORD) Form W	/WC-5	KSA 82a-12	12			
LOCATION OF W		Fraction			Section	Number	Township Nu	mber	Range	Number
inty:	Riley	NE ¼	NE ¼	NE ½	<u>'</u>	18	т 10	S	R	<u>8</u> Е
ance and direction	from nearest to	own or city street add	4 - 4 rc	ated within	city?	'e				
	WED CM O	121	1015143	St. Man	ilalian, n			· · · · · · · · · · · · · · · · · · ·	·	
WATER WELL OV			200m 2806				Doord of Agrico	dturo Divi	nion of Mot	or Possuroos
#, St. Address, Bo	x# : 9 Gie	enway Plaza, I ton, TX 77046	100111 2800				Board of Agrica		SIUII UI VVA	ei Resources
, State, ZIP Code	CATON WIT	H					Application Nu	nber.		
OCATE WELL'S AN "X" IN SECTIO	N BOX:	" 4 DEPTH OF C	OMPLETED WE	LL	67.5	ft. ELEVA	TION:			
	N	Depth(s) Groundy								
		WELL'S STATIC								
NW	NE						after			
!	T:	Est. Yield								
w		E Bore Hole Diamet	er 8.625 i	n to	67.5	' `` f	t and	in	to	Ft.
''		WELL WATER TO 1 Domestic	BE USED AS:	5 Public	water supp	oly	8 Air condition	ing 11	Injection	vell
SW	SE	1 Domestic	3 Feed lot	6 Oil fiel	d water sur	ply	9 Dewatering	12	Other (Sp	ecify below)
	." }	2 Irrigation	4 Industrial	7 Lawn a	and garden	(domestic)	10 Monitoring	well	MW	<i>l</i> -26
<u> </u>		Was a chemical/b	acteriological sa	mple subm	itted to Der	artment? Y	es No X	If yes,	mo/day/yr :	sample was
	S	Submitted	<u> </u>				r Well Disinfected			
TYPE OF BLANK	CASING USED:		5 Wrought Iro	n 8	Concrete	tile				
1 Steel	3 RMF		6 Asbestos-C					Welde		
2 PVC	4 ABS		7 Fiberglass		, .	•			ded	Χ
			F.							
nk casing diamete	2	in. to 20	Dia		In. to		ft., Dia		in. to	ft.
sing height above I	and surface	FLUSH	n., weight	SCH	40	Lbs./ft. \	Wall thickness or	gauge No.		
PE OF SCREEN C	R PERFORATION	ON MATERIAL:				/C	10 Ache	toe-come	of.	
1 Steel	3 Stair	less steel	5 Fiberglass		8 RM	ЛР (SR)	11 Other 12 None	(specify)		
2 Brass	4 Galv	anized steel	6 Concrete tile	Э	9 AE	BS	12 None	used (ope	n hole)	
REEN OR PERFO	RATION OPEN	NGS ARE:	5	Gauzed wr			8 Saw cut		11 None (open hole)
1 Continuous s	lot 3	Mill slot	6	Wire wrap	oed		9 Drilled holes			
Louvered shu	itter 4	Key punched		Torch cut			10 Other (specif	y)		
REEN-PERFORAT	ED INTERVALS	S: From	20 ft. to		67.5	ft. Fro	om	ft. to		ft.
							om			
SAND PACK	INTÉRVALS:	From	18 ft. to		67.5		om			Ft.
		From	ft. to				om			Ft.
GROUT MATERIA	L: 1 Near	cement 2	Cement grout			ite 4	Other			
			Ft.		Ft.					
		ft. to 16								
	ource of possible	contamination: 4 Lateral lines	7 Pit			10 Livesion	ck pens		well/ Gas w	
1 Septic tank							•			
2 Sewer lines		5 Cess pool		wage lago		12 Fertilize	-		er (specify l	
3 Waterlight se	wer lines	6 Seepage pit	9 Fe	edyard			ide storage	Cor	ntaminat	ea Site
ection from well?	1001			Ι.		low many fe		20112	TED. /	
ROM TO	CODE		GIC LOG		ROM	ТО	PLU	JUING IN	TERVALS	
0 1		ravel/Grass/To	psoil							
1 8 8 18		ilty Clay								
8 18 18 67.5		andy Clay and								
67.5 TD		nd of Borehole								
,,,,	<u> </u>	ila of Bolefiole	·	-						
		1								
001751075	251425	DIO OFFICIALE	NI. TL' '			1 (2)	structed == (0)			Intion ====
		R'S CERTIFICATIO								
		06/10	/ 14 		And this r	ecora is trui	e to the best of m	y knowledo	ge and belie	et. Kansas
			585				ord was complete			
er the business na		Associate				By ·	(signature) Bra	aley J.	Jonnso	<u>n</u>
INSTRUCTIONS:, Kansas 66620-000	riease till in blan 1. Telephone: 9	ks and circle the correction 13-296-5545. Send or	answers. Send to WATER WFI	urree copies L OWNER :	ιο Nansas I and retain or	pepartment one for your re	or meaith and Environments.`	onment, Bur	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	г, горека,