- <b>)</b>	<del></del>			R WELL RECORD	Form W\		KSA 82a-1			nga Nicosia	
	ON OF WATE		ı	NE ¼	SW 1/4		n Number 18	Township Number	l l	ange Number <b>8</b>	Е
County Distance and		ley m nearest to	SW ½ own or city street add				10	10	S   R	8	듸
vistance and	a anection no	ealest (C	omit of only street add	1629 Poyntz			KS				_
			s Automotive :	Service							
			Poyntz Ave.					Board of Agricultur	e, Division of	Water Resource	es
city, State, 2	ZIP Code	Manh	attan, KS 6650	)2				Application Number	er:		_
LOCATE	WELL'S LOC SECTION B	CATON WIT	H 4 DEPTH OF CO	MPI ETED WEI	ı	30	ft FLF\	/ATION·	1042.3	3	İ
704 7 11.	N	OX.	Denth(s) Grounds	vater Encountere	 d 15	25	- 10. <b>C</b> _C_	/ATION:	ft. 3		Ft.
<b>A</b>	i I	- ; -	WELL'S STATIC	MATER I EVEL	25.36	ft he	low land s	urface measured on m	o/dav/vr	10/09/14	Ft.
	!w <b>_</b> _	. NE						t. after h			m
-		!						t. after +			m
N ⊠ie			E Bore Hole Diamet	er <b>8.5</b> li	n to	30		ft and	in. to	,	Ft.
7			WELL WATER TO	BE USED AS:	5 Public v	water supp	oly	ft. and 8 Air conditioning 9 Dewatering	11 Inject	ion well	
-	_s/.X	_ SE	1 Domestic	3 Feed lot	6 Oil field	l water su	pply	9 Dewatering	12 Othei	r (Specify below	/) 
			_					c) 10 Monitoring wel			
` <u>L</u>	S		Was a chemical/b	acteriological sa	mple submit	ted to Dep	partment?	Yes No X	If yes, mo/day	• • •	;
		·····	Submitted					ter Well Disinfected?	***************************************		
5 TYPE OF	BLANK CAS	SING USED:		5 Wrought Iro				CASING JOINTS:		Clamped	
1 Ste	el	3 RMF	P(SR)	6 Asbestos-C	ement 9	Other (sp	ecify belo	w)	Welded		
2 PV	2	4 ABS		7 Fiberglass			<b>-</b>		Threaded	X	
Dlank agains	diameter	2	in. to 20	Ft.,		In to		ft., Dia	in to		ft.
Daeina beial	ht ahove land	surface	FLUSH •	n wejaht	SCH 4	40	l hs /ft	Wall thickness or gau	ige No.		-
			ON MATERIAL:	ii., weigiit		7 P	√C	10 Asbestos	-cement		
1 Ste				5 Fiberglass				11 Other (sp			
2 Bra			anized steel	6 Concrete tile		9 AE	BS (F)	12 None use	ed (open hole)		
SCREEN OF	R PERFORA	TION OPEN	INGS ARE:	5	Gauzed wra	apped		8 Saw cut	11 No	one (open hole)	
1 Cor	ntinuous slot	3	Mill slot	6	Wire wrapp	ed		9 Drilled holes			
2 Lou	vered shutter	. 4	Key punched		Torch cut			10 Other (specify)			
SCREEN-PE	ERFORATED	INTERVAL						rom			
			From	ft. to			ft. F	rom	<sup>ft. to</sup>		Ft.
SAN	ID PACK INT	ERVALS:	From					rom			
			From					rom			Ft.
6 GROUT	MATERIAL:	1 Nea	t cement 2			3 Bentor	nite	4 Other			
Grout Interv	als From2	0.5	ft. to 16	Ft. From3	16	Ft. to	18	ft. From	ft. to	•	ft.
			e contamination:					tock pens			
1 Sep	tic tank	•	4 Lateral lines	7 Pi	t privy		11 Fuel:	storage	15 Oil well/ G	as well	
2 Sev	ver lines		5 Cess pool	8 Se	ewage lagoo	on	12 Fertili	zer storage	16 Other (spe	cify below)	
3 Wa	tertight sewer	lines	6 Seepage pit	9 Fe	edyard		13 Insec	ticide storage	Contam	inated Site	
Direction fro	m well?					}	low many	feet?			$\sqcup$
FROM	то	CODE		OGIC LOG	F	ROM	то	PLUGG	ING INTERV	ALS	
0	0.666		oncrete (8")								
0.666	30	S	ilty Clay					112.47.			_
30	TD	E	nd of Borehol	9			-		***************************************		
											$\dashv$
		<u> </u>						,			
		<del>                                     </del>									_
		<del>                                     </del>	,		<del></del>						_
7 CONTRA	CTOR'S OR	LANDOWN	ER'S CERTIFICATION	ON: This water w				onstructed, or (3) plugg			
	on (mo/day/yr		10/07					rue to the best of my k			
	Contractor's L			585			ter Well Re	ecord was completed of	on (mo/day/yr)	10/31/14	ļ
rider the hi	isiness name	of	Associate	ed Environn	nental, Ir	ıc.	E	by (signature) Brad	iey J. Joh	nson	
INSTRU	JCTIONS: PI	ease fill in bla	nks and circle the corre 913-296-5545. Send o	ect answers. Send	three copies	to Kansas	Departmen	nt of Health and Environm	nent, Bureau of	Water, Topeka,	
nansas	. 00020-0001.	releptione.	710-200-0040. Selid 0	IN IN TANIEN WE		ICIEIII C	o. your	D		) /	_
								Di	act to		
								w	011		

٠,