SEC

					VELL RECO	ORD For			32a-1212			- revise	
1 LOCATIO					\(\A/	614		tion Num	1	Township N		Range Numbe	- 1
County:		iley	SE own or city stre		NW ½			18		T 10	S	R 8	E
Distance and	a direction fro	m nearest to	own or city stre	eet addres 102	26 Poynt	z Avenu	e, Ma nha	ttan, K	S				
2 WATER V	VELL OWNE	R: RVR	Property,										
			Poyntz A						i	Board of Agric	ulture, Divi	sion of Water Reso	urces
City State 7	IP Code	Manh	nattan, KS	66502						Application Nu	ımber:		
, LOCATE	WELL'S LOO SECTION B	CATON WIT	H 4 DEPTH	OF COM	IPLETED V	VELL	30	ft. I	ELEVATI	ON:	1	018.24	
	N		Depth(s) G	iroundwat	er Encount	ered 1.5	2	5 	ft. 2		ft.	3	Ft. Gpm Gpm
†		i										yr 10/12/1 5	5
	NW	NE		Pump tes	st data: V	Vell water v	was		Ft. af	ter	hours p	oumping	Gpm
υ U			Est. Yield		Gpm: V	Veil water v	was		Ft. af	ter	Hours p	oumping	Gpm
₹ W -	-	+	E Bore Hole	Diameter	8.5	In. to	3(0	ft. a	and	in	i. to 1 Injection well 2 Other (Specify be	Ft.
	X 'v	_ SE	1 Doi	mestic 3	Feed lot	is: 5 Pu 6 Oil	field water	uppiy supply		9 Dewatering	11 12 1	2 Other (Specify be	elow)
<u> </u>			2 Irrig	gation 4	1 Industria	l 7 La	wn and gard	den (don	nestic)	10 Monitoring	well	MW-4	
†		!										mo/day/yr sample	was
	S		Submitted		ŭ	•		·		Vell Disinfecte		.,	
5 TYPE OF	BLANK CAS	SING USED:		5	Wrought	Iron	8 Concr	ete tile		CASING JOIN	NTS: Glue	d Clamped	
1 Stee		3 RMF		6	Asbesto	s-Cement	9 Other				Weld		
2 PVC	;	4 ABS		7	Fiberglas	ss					Threa	aded X	
		_ ,		20	Ft.,								
			in. to		Dia							in. to	
			FLUSH ON MATERIA		weight					10 Asbe		·	
1 Stee			on Materia Hess steel		Fiberglas	35							
2 Bras			anized steel		Concrete		9	ABS	,,,	11 Othe 12 None	e used (ope	en hole)	
SCREEN OF	R PERFORA	TION OPEN	INGS ARE:			5 Gauze	d wrapped		8			11 None (open ho	ole)
1 Con	tinuous slot	3	Mill slot			6 Wire w	rapped			Drilled holes			
2 Louv	vered shutter	r 4	Key punche			7 Torch			10	Other (spec	ify)		
SCREEN-PE	RFORATED	INTERVAL										0	
					ft.							o	
SAN	D PACK INT	ERVALS:	From	10			30					o	
61			From	T		to							Ft.
			t cement		Ft	_	Et	tonite					
Grout Interva	ls From2	0.5	ft. to	16	From3	16	to		18	ft. From		ft. to	ft.
			e contaminatio									andoned water well	
1 Sept	tic tank		4 Lateral	lines	7	Pit privy		11 F	-uel stora	ige	15 <u>Oil</u>	well/ Gas well	
2 Sew			5 Cess po			Sewage la	agoon		ertilizer :	•		ner (specify below)	
	ertight sewer	lines	6 Seepag	ge pit	9	Feedyard				e storage	Co	ntaminated Si	te
Direction from		6655		THO! OO	10.1.00		FDC::		nany feet		1001110	ITED VALO	
FROM 0	TO	CODE		THOLOG			FROM	то	<u>'</u>	PL	JGGING IN	ITERVALS	
0.5	0.5 30		oncrete P	arking	Drive								
30	TD		nd of bore	ehole				1					
								+					
						-		+					
7 CONTRAC	CTOR'S OR	LANDOWN	ER'S CERTIF	ICATION:	This water	r well was	(x) constru	cted (2)	reconstru	ucted or (3) o	lugged und	ler my jurisdiction ar	nd w
Completed or	n (mo/day/vr	DOTTI	O OLIVIII I	10/08/1	5	#43	And th	is recom	is true t	o the best of r	nv knowled	ge and belief. Kans	sas
Water Well C	Contractor's I	icense No		5	85		This W	/ater We	all Record	was complete	ed on (mo)	day/yr) 11/06/	15
under the bus			Asso									Johnson .	<i>:</i>
INSTRU	CTIONS: Ple	ease fill in blar	nks and circle th	ne correct a	inswers. Se	end three co	pies to Kans	as Depar	tment of h	lealth and Envi	rongent, Bu	of Water, opek	
Kansas 6	66620-0001.	Telephone: 9	13-296-5545.	Send one t	o WATER V	VELL OWN	ER and retain	n one for	your reco			a lohusa	