WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: Fraction Township Number Section Number Range Number NE ½ SW NW 1/4 18 10 8 Distance and direction from nearest town or city street address of well if located within city? 1026 Poyntz Avenue, Manhattan, KS 2 WATER WELL OWNER: RVR Property, LLC RR#, St. Address, Box # : 1020 Poyntz Avenue Board of Agriculture, Division of Water Resources : Manhattan, KS 66502 City, State, ZIP Code Application Number: **30** ft. ELEVATION: **1019.29** Depth(s) Groundwater Encountered 1.5 **25** ft. 2 ft. 3 Ft. WELL'S STATIC WATER LEVEL 24.64 ft. below land surface measured on mo/day/yr 10/12/15 - NE -Pump test data: Well water was Ft. after hours pumping Gpm NW\_ Est. Yield Gpm: Well water was Ft. after Hours pumping Gpm
Bore Hole Diameter 8.5 In. to 30 ft. and in. to Ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) X 9 Dewatering 1 Domestic 3 Feed lot 6 Oil field water supply 12 Other (Specify below) SW. SF .. 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well MW-3 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was Water Well Disinfected? Yes Submitted 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tite CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 1 Steel 3 RMP (SR) 4 ABS 7 Fiberglass Threaded X .\_\_\_\_\_ Ft.. Blank casing diameter 2 in. to 20 Dia In. to ft., Dia in. to ft.

Casing height above land surface FLUSH In., weight SCH 40 Lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 11 Other (specify) 8 RMP (SR) 3 Stainless steel 5 Fiberglass 1 Steel 9 ABS 4 Galvanized steel 6 Concrete tile 12 None used (open hole) 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 11 None (open hole) 5 Gauzed wrapped 8 Saw cut 6 Wire wrapped 1 Continuous slot 3 Mill slot 9 Drilled holes 10 Other (specify) 2 Louvered shutter 4 Key punched 7 Torch cut From **20** ft. to **30** ft. From ft. to ft. SCREEN-PERFORATED INTERVALS: 
 From
 ft. to
 ft. From
 ft. to
 Ft.

 From
 18
 ft. to
 30
 ft. From
 ft. to
 Ft.
 SAND PACK INTERVALS: ft. From ft. to 3 Bentonite 6 GROUT MATERIAL: 2 Cement grout 1 Neat cement 4 Other Grout Intervals From 2 0.5 ft. to 16 From 3 16 to 18 ft. From ft. to What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 15 Oil well/ Gas well 1 Septic tank 7 Pit privy 11 Fuel storage 4 Lateral lines 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Contaminated Site Direction from well? How many feet? CODE LITHOLOGIC LOG FROM PLUGGING INTERVALS FROM TO TO æ 0 0.5 **Gravel Drive** Silty Clay 0.5 30 30 TDEnd of borehole 7 ICONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (x) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and w Completed on (mo/day/yr) 10/08/15 And this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 11/06/15 INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Buy and office of Foreign (Ransas 66620-0001). Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.