


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 SW 1/4 Section Number #26 Township Number T 10 S Range Number R 8 E
County: RILEY
Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: HOWARD BECKMANN
RR#, St. Address, Box #: 1021 E 26th AVE (Rt 3) Board of Agriculture, Division of Water Resources
City, State, ZIP Code: MANHATTAN, KS 66502 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. 40 ft. 2. 16 ft. 3. 16 ft.
WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr 9/16/91
Pump test data: Well water was 40 ft. after 16 hours pumping 16 gpm
Est. Yield 16 gpm: Well water was 40 ft. after 16 hours pumping 16 gpm
Bore Hole Diameter 4 in. to 11 ft., and 11 in. to 11 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X
2 PVC 4 ABS (Rock) 7 Fiberglass 8 Galvanized Steel Threaded X
Blank casing diameter 3 1/2 in. to 11 ft., Dia 8 in. to 60 ft., Dia 11 in. to 11 ft.
Casing height above land surface 11 in., weight 11 lbs./ft. Wall thickness or gauge No. 11
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 11
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 11
SCREEN-PERFORATED INTERVALS: From N/A ft. to N/A ft., From N/A ft. to N/A ft.
GRAVEL PACK INTERVALS: From N/A ft. to N/A ft., From N/A ft. to N/A ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 11
Grout Intervals: From 19 ft. to 11 ft., From 11 ft. to 11 ft., From 11 ft. to 11 ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage NONE

Direction from well? How many feet?
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
60 40 Chlorinated SAND
40 19 Subsoil
19 11 BENTONITE
11 0 SOIL

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/16/91 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. KS4 This Water Well Record was completed on (mo/day/yr) 9/24/91
under the business name of KS4 by (signature) Danny H. Rogers