

WATER WELL RECORD Form WWC-5 KSA 82a-1212					
1 LOCATION OF WATER WELL: County: Pott.		Fraction Center of ¼ S.W. ¼	Section Number 13	Township Number T 10 S	Range Number R 9 E/W
Distance and direction from nearest town or city street address of well if located within city? 3 miles west of Wamego on Military Trail Rd. and 1/4 mi. south					
2 WATER WELL OWNER: Thomas L. Ebert RR#, St. Address, Box # 11650 Louisville, Rd. City, State, ZIP Code :St. George, Ks. 66535			Board of Agriculture, Division of Water Resources Application Number: 41,552		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL . 65 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 19 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr 4-18-95			
		Pump test data: Well water was 29 ft. after 1 hours pumping 1200 gpm			
		Est. Yield 2000 gpm: Well water was 36 ft. after 1 hours pumping 1400 gpm			
		Bore Hole Diameter 32 in. to 65 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
				2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No ^{XX} ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No ^{XX}					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 16 in. to 45 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. 50					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 45 ft. to 65 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 65 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) How many feet?					
Direction from well?					
FROM		TO		LITHOLOGIC LOG	PLUGGING INTERVALS
0		3		Brown top soil	
3		25		Brown silty sand	
25		35		Medium-large grey gravel	
35		64		Medium-large brown gravel	
64		65		Weathered shale, stopped	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (+) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-19-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 323 This Water Well Record was completed on (mo/day/yr) 5-16-95 by signature Dan Hoobler under the business name of Hoobler Drilling Co.					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					