


1 LOCATION OF WATER WELL: Fraction NE 1/4 SE 1/4 N13/4 Section Number 28 Township Number T 11 S Range Number R 10 E
 County: Wabasha Co.
 Distance and direction from nearest town or city street address of well if located within city? From Alma go 3/4 mile North 1/4 of a mile West on Hinckville Rd + 1/4 South on Priddy Creek Rd.

2 WATER WELL OWNER: Jim Garet
 RR#, St. Address, Box #: 362177 Anolop Circle
 City, State, ZIP Code: Alma, KS 66401
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 170 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 142 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 130 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 15 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 150 ft. Dia in. to ft. Dia in. to ft.
 Casing height above land surface 2' in., weight Sch 40 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 150 ft. to 170 ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 170 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 5 ft. to 25 ft. From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil	142	153	Limestone (Water)
1	22	Brown Clay	153	156	Grey shale
22	31	Limestone	156	168	Limestone
31	54	Brown shale	168	170	Grey oily shale
54	62	Limestone			
62	73	Grey shale			
73	85	Brown shale			
85	88	Limestone			
88	93	Grey shale			
93	110	Limestone			
110	123	Grey shale			
123	131	Limestone			
131	142	XI Clear shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION. This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/18/2005 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 451 This Water Well Record was completed on (mo/day/yr) 1/28/2005 under the business name of Holdeman Well Drilling by (signature) Wray H. Cudde