

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.


1 LOCATION OF WATER WELL: County: WABAUNSEE Fraction SW 1/4 SW 1/4 NE 1/4 Section Number 36 Township Number T 11 S Range Number R 11 EW

Distance and direction from nearest town or city street address of well if located within city? 1 EAST, 3/4 SOUTH & 3/4 EAST OF PAXICO

Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: K BAR N LLC. RR#, St. Address, Box #: 12550 N. MENNONITE RD. City, State, ZIP Code: GARDEW, CITY 67846

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N



4 DEPTH OF COMPLETED WELL: 120 ft. Depth(s) Groundwater Encountered: 57 ft. WELL'S STATIC WATER LEVEL: 57 ft. below land surface measured on mo/day/yr. 3/31/11. Pump test data: Well water was... Est. Yield: 10 gpm. WELL WATER TO BE USED AS: 12 Other (Specify below) LIVE STOCK. Was a chemical/bacteriological sample submitted to Department? No. Water well disinfected? No.

5 TYPE OF CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought Iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below). CASING JOINTS: Glued, Clamped, Welded, Threaded.

Blank casing diameter: 5 in. to 10.0 ft., Diameter: in. to ft., Diameter: in. to ft. Casing height above land surface: 1.8 in., Weight: 2.00 lbs./ft. Wall thickness or guage No.: 2.65

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RM (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw Cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft., From 100 ft. to 120 ft., From 30 ft. to 120 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 5 ft. to 30 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer Storage, 13 Insecticide Storage, 14 Abandoned water well, 15 Oil well/gas well, 16 Other (specify below)

Direction from well? WEST How many feet? 100

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-14 BROWN CLAY, 14-17 RED SHALE, 17-19 YELLOW SHALE, 19-40 GRAY SHALE, 40-42 LIMESTONE, 42-87 GRAY SHALE, 87-94 LIMESTONE, 94-98 GRAY SHALE, 98-101 LIMESTONE, 101-106 GRAY SHALE, 106-109 RED SHALE, 109-120 GRAY SHALE.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/31/11 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 51.8 This Water Well Record was completed on (mo/day/year) 4/15/11 under the business name of BLUE VALLEY DRILLING INC (signature) Eric [unclear]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.