


1 LOCATION OF WATER WELL: County: WADSWORTH Fraction: NW 1/4 SE 1/4 SE 1/4 Section Number: 15 Township Number: T 11 S Range Number: R 11 E/W

Distance and direction from nearest town or city street address of well if located within city? From Allen Co North 8 miles
Thin @ East 1 mile + North 1 mile

2 WATER WELL OWNER: Wheat Ranch
 RR#, St. Address, Box #: RR Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Allen, KS 66833 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 110' ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 9.5 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 80 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 100 gpm; Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 9 in. to 110' ft., and in. to ft.
 WELL WATER TO BE USED AS: Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 5 Public water supply 8 Air conditioning 11 Injection well
 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 5 Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded
 Blank casing diameter: 5 in. to 90 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface: 2 in., weight Sch 40 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 3 Mill slot 25/1000 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 90 ft. to 110 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 2.5 ft. to 110 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 2.5 ft., From Empty ft. to ft.
 What is the nearest source of possible contamination: None Close
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	8	Brown Shale			
8	11	Greenish Shale			
11	16	Yellow Shale			
16	19	Limestone			
19	31	Brown Shale			
31	38	Grey Shale			
38	41	Limestone			
41	50	Grey Shale			
50	66	Brown Shale			
66	78	Limestone			
78	85	Grey Shale			
85	95	Brown Shale			
95	102	Limestone (Water)			
102	110	Brown Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/8/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451 This Water Well Record was completed on (mo/day/yr) 10/8/91 under the business name of Holman Well Drilling by (signature) Craig H. Ford/PT