USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

ok.

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction	-	Section	number	Township number	Range number		
1. Location of well:		· ` •	1/4					E/W	
2 Distance and direct	Shawnee	SW 1/4 NE 1/4 NE		er of well	l. Doha	T 11S s	R 13E	E/W	
2. Distance and direction from nearest town or $\frac{1}{2}$: mi. E. of Rossville. Owner of Ks., on U.S.24, $\frac{1}{4}$ mi.N., & $\frac{1}{4}$ mi. E. Street address of well location if in city:						ert mela			
Street address of well location if in city: City, s					state, zip code: Rossville, Ks. 66533				
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. 30 in. Completion date 12-20-77			
, , , , , , , , , , , , , , , , , , ,				11		Well depth 64 ft.			
				\		7 Cable tool _ Rotary			
						Hollow rod Jetted Bored Reverse rotary			
				(Jr Ur		8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock Lawn Oil field water Other			
sw	SE Pass.	ALL A		3		9. Casing: Materia Trans		low	
t		The state of the s		>		Threaded Welded RMP PVC		in. _lbs./ft.	
1 Mi		14.5 24	+++	Home	.	Dia 16 in. to 38 ft. dep			
5. Type and color of material				From	To	Dia in. to ft. dep			
				 		10. Screen: Manufacturer's r Johnson Well Ca	asing Co.		
Dark brown silt				0	8	Type Transite	Dia, 16"		
Fine hours and				8	277	Slot/gauz 1/8 x 8	_ Length		
Fine brown sand				0	27	Set between 38	ft. and64	— ft.]	
Med. brown sand & gray silt				27	39	Gravel pack? Yes Size range of material 1/8-1/4"			
Med. to large gray gravel				39	52	11. Static water level: mo./day/yr. 2012 ft. below land surface Date 12-20-77			
ned, to large gray graver					-)-//	
Large gray gravel				52	64	12. Pumping level below land 26 ft. after 1 h		g.p.m.	
Stopped.				64		30 ft. after3 i	nrs. pumping 1 <u>000</u>	g.p.m.	
	*					Estimated maximum yield	1200	g.p.m.	
				-		 Water sample submitted: Yes X No 	mo./ Date	/day/yr.	
						14. Well head completion:			
						Pitless adapter	Inches above g	rade	
				_		15. Well grouted?	, Y		
					With: Neat cement Bentonite X Concrete Depth: From 0 ft. to 10 ft.			oncrere	
						16. Nearest source of possible	contamination: hou	ise_	
						ft. 800 Direction	Typelate	rals X No (
					 	Well disinfected upon completed 17. Pump:	X Not installed	-1 \wedge	
						Manufacturer's name	1401 Histories	r.	
						Model number			
						Length of drop pipe Type:	tt. capacity	g.p.m.	
						Submersible	Turbine		
	(Lie a second e	heet if needed)	-			Jet Centrifugal	Reciprod Other	cating S	
(Use a second sheet if needed) 18. Elevation: 19. Remarks:						20. Water well contractor's		— ° /	
924 1						This well was drilled under my jurisdiction and this report			
727 Topography:						is true to the best of my knowledge and belief.			
—— Hill						Hoobler Drilling Co. 323 Business name License No.			
Slope						Address St. Marys	i. Ks.,66536		
Upland _X_ Valley						Signed Ruthorized rep	Date -	1-5-78	