USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

) Cou	unty	Fraction Ctr. of		Section	number	Township number	Range number		
W	Shawnee		SE. 1/4	5	į	T # 115 s	R 13	(E/)W	
Distance and direction	from nearest town or city	West 1 mi.		ner of well		vid Stadler			
	- West of Rossvil	lle. Ks. Gm	1	street:	Do	aggrilla Vanca	s 66536		
					tate, zip code: Rossville, Kansas 66536 6. Bore hole dia. 30 in. Completion dat 10-9-76				
4. Locate with "X" in section below: Sketch map:						Well depth 47ft.			
NW NE						7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored X_ Reverse rotary			
						8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock Lawn Oil field water Other 9. Casing: Material Trans Height Above or below Threaded Welded Surface in.			
									W SW X E J J J J J J J J J J J J J J J J J J
5 1——— 1 Mile —	KS, Reven								RMP PVC Dia.16_ in. to 21_ ft. de
5. Type and color of mater	rio	<u> </u>		From	То	Dia in. to ft. de	pth gage No. 1/8		
						10. Screen: Manufacturer's	name Johnson We	ell	
Top soil & fine sand				0	2	Type Transite	Dia. 16"		
Fine brown sand			2	4	Slot)gauze 1/8x8 Set between 47	Length <u>26 </u>	ft.		
Soft brown clay			4	7		and	ft.		
					1			day/yr.	
Fine brown sand & brown clay				7	12	11. Static water level: 20 1 311 ft. below land so	urface Date 10-9-	76	
Hard gray sand & stone				12	18	12. Pumping level below lar 25 ft. after 1		g.p.m.	
Small to med. brown gravel				18	22	25 ft. after 1 hrs. pumping 800 g.p.m. 800 g.p.m.			
Fine to med green gravel				20	25	Estimated maximum yield 13. Water sample submitted:		g.p.m. day/yr.	
Fine to med. green gravel				22	22	Yes X No	•	,, ,	
Med. brown gravel				25	27	14. Well head completion: Pitless adapter	Inches above gr	ade	
Med. green gravel				27	28	15. Well grouted? Yes			
Med. to large green gravel				28	47	With: Neat cement Depth: From ft. to	BentoniteX_ Co	oncrete	
Stopped.						16. Negrest source of possib	le contamination:		
2				47		ft. 2000 Direction	Outh Type rive	ar	
						Well disinfected upon comp 17. Pump:	X Not installed	140	
						Manufacturer's name			
						Model number		g.p.m.	
						Туре:			
						Submersible Jet	Turbine Reciproc	ating	
	(Use a second s	heet if needed)	~			Centrifugal	Other		
18. Elevation: 19. Remarks: Set up for center pivot.						20. Water well contractor's This well was drilled under		eport	
3 Rim		_				is true to the best of my kno	wledge and belief.	3	
Topography:Hill	we do not	install pumps.	•			Hoobler Drilli			
Slope						Address St. Wary	s, Ks. 66536		
Upland						Signed Authorized re	presentative Date	 22	