WAICH WELLI		Division of Water Resources App. No. 7765-
1 LOCATION OF V	VATER WELL: Fraction J n e	Section Number Township Number Range Number 177 T // S R /4 DE DW
Street/Rural Address of V	Vell Location: if unknown distance & direction	Global Positioning System (GPS) information:
from nearest town or inte	rsection: If at owner's address, check here \square .	Latitude: (in decimal degrees) Longitude: (in decimal degrees)
		Elevation:
2 WATER WELL C	OWNER: Clark Bros	Datum: UWGS 84, UNAD 83, UNAD 27
RR#, St. Address, I		Collection Method:
City, State, ZIP Co		
	Silver Loke As 66539	☐ GPS unit (Make/Model: ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
3 LOCATE WELL		
WITH AN "X" IN	4 DEPTH OF COMPLETED WELL	68 ft.
SECTION BOX:		ft. (2) ft. (3) ft.
N	WELL'S STATIC WATER LEVEL	ft. below land surface measured on mo/day/yr
	Pump test date: Well water was	ft often hours numing
1 1	Tump test data. Well water was	ft. after hours pumping gpm
NW NE	gpm: Well water was	ft. after hours pumping gpm
w — —	E WELL WATER TO BE USED AS: ☐ Public	water supply Geothermal Injection well Supply Dewatering Other (Specify below)
	Domestic Feedlot Oil field water s	supply
SW SE	☑ Irrigation ☐ Industrial ☐ Domestic-lawn	
	Was a chemical/bacteriological sample submitted	to Department? \(\sigma\) Yes \(\overline{\overline{\overline{N}}}\) No
S	If yes, mo/day/yr sample was submitted	·
1 mile	Water Well Disinfected? ☑ Yes ☐ No	
CASING IOINTS: IX	USED: ☐ Steel ☑ PVC ☐ Other I Glued ☐ Clamped ☐ Welded ☐ T 16 in to 28 ft. Diameter	henodod
Casing diameter	16 in to 28 ft Diameter	in to ft Diameter in to ft
Casing height above is	and surface 24 in Weight	in. to ft., Diameter in. to ft. 16.15 lbs./ft. Wall thickness or gauge No500
TYPE OF SCREEN OR	PERFORATION MATERIAL:	10.15 ibs./it. Wan tilickness of gauge No
□ Steel		Other (Specify)
	☐ Galvanized Steel ☐ None used (open hole)	Other (Specify)
SCREEN OR PERFORATION OPENINGS ARE:		
	☐ Mill slot ☐ Gauze wrapped ☐ To	rch cut
☐ Louvered shutter	☐ Key punched ☐ Wire wrapped ☒ Sa	w cut
SCREEN-PERFORATE	DINTERVALS: From 28 ff. t	o 68 ft From ft. to ft. l
	From ft. t	o ft., From ft. to ft.
GRAVEL PACK	INTERVALS: From 20 ft. t	o 68 ft., From ft. to ft.
	From ft. t	o ft., From ft. to ft. o 68 ft., From ft. to ft. o ft. o ft., From ft. to ft.
6 GROUT MATERIA	I. Neat cement Cement grout	Bentonite
Grout Intervals Fro	om 0 ft to 20 ft From	ft. to ft. From ft. to ft.
What is the nearest source	ee of possible contamination:	16. to 16. 110m
☐ Septic tank		vestock pens
☐ Sewer lines	☐ Cesspool ☐ Sewage lagoon ☐ Fu	el storage
☐ Watertight sewer	lines \square Seepage pit \square Feedyard \square Fe	rtilizer storage
Direction from well		tance from well
FROM TO		ROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS
	Topsoil 1	ROM TO ETITIO. EOG (CORE.) OF T ECCORTO HATERATES
	Clay	
	Med sand & course gravel	
	The second of th	
	4	
	Visit in the second sec	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was reconstructed, or □ plugged		
under my jurisdiction and was completed on (mo/day/year) 11/16/11 and this rec The best of my knowledge and belief.		
Kansas Water Well Contractor's License No. 554 . This Water Well Record was completed on (mo/day/year) 11/22/11		
under the business name of Woofter Pump & Well Inc. by (signature)		
INSTRUCTIONS: Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to kansas Department of Heath and Environment, Bureau of		
Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.		