


1 LOCATION OF WATER WELL: Fraction NE 1/4 SE ~~SW~~ 1/4 SW 1/4 Section Number 10 Township Number T 11 S Range Number R 14 E/W  
 County: Shawnee

Distance and direction from nearest town or city street address of well if located within city?  
 1/2 mile east of the N.E. corner of Silver Lake Ks.

2 WATER WELL OWNER: Vernon C. Wyatt  
 RR#, St. Address, Box #: 8642 N.W. 21 st. R.R 6 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Topeka, Ks. 66608 Application Number: 39,861

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 49' 8" ft. ELEVATION: 10-24-90 ft.  
 Depth(s) Groundwater Encountered 1 18 ft. 2 . ft. 3 . ft.  
 WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was 32 ft. after 1 hours pumping 600 gpm  
 Est. Yield 1000 gpm: Well water was 43 ft. after 2 hours pumping 800 gpm  
 Bore Hole Diameter: 32 in. to 49 ft., and . in. to . ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes.....No...xx.....; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No xx

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ..xx.. Clamped ..  
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded ..  
 2 PVC 4 ABS 7 Fiberglass Threaded ..  
 Blank casing diameter 16 in. to 29 ft., Dia . in. to . ft., Dia . in. to . ft.  
 Casing height above land surface 12 in., weight . lbs./ft. Wall thickness or gauge No. .65  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 2 PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) ..  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ..  
 SCREEN-PERFORATED INTERVALS: From 29 ft. to 49 ft., From . ft. to . ft.  
 From . ft. to . ft., From . ft. to . ft.  
 GRAVEL PACK INTERVALS: From 18 ft. to 49 ft., From . ft. to . ft.  
 From . ft. to . ft., From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 18 ft., From . ft. to . ft., From . ft. to . ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage none

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Brown clay and silts			
4	14	Grey clay			
14	19	Brown silt			
19	24	Brown clay			
24	33	Medium brown gravel and clay lenses			
33	48	Large brown gravel			
48	49	Weathered shale, stopped			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-22-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. ~~10-22-90~~ 323 This Water Well Record was completed on (mo/day/yr) 10-24-90 under the business name of Hoobler Drilling Co. by (signature) *Don Hoobler*

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY  
T  
R  
EW  
SEC.  
1/4  
1/4  
1/4