USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

Vjá

WATER WELL RECORD KSA 82a-1201-1215

11

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	3				peka, Kanaas oooto	
County	Fraction NW SW	Section	number	Township number	Range number	
1. Location of well: Shownee	5E 145E 145#1	4	3/	т //	s R 15	E/W
2. Distance and direction from nearest town or city: 2. Distance and direction from nearest town or city: 2. Distance and direction from nearest town or city: 2. Distance and direction from nearest town or city: 3. Owner of well: CURT Schaeffer R.R. or street: 3346 N.W. Bzicky ARd City, state, zip code: 2. Distance and direction from nearest town or city: 2. Distance and direction from nearest town or city: 2. Distance and direction from nearest town or city: CURT Schaeffer R.R. or street: 3. Owner of well: Curt Schaeffer R.R. or street: 3. Owner of well: Curt Schaeffer R.R. or street: 3. Owner of well: Curt Schaeffer R.R. or street: 3. Owner of well: City, state, zip code: 3. Owner of well:						
Street address of well location if in city:				346 N.W.BZ	ickunad	
Street address of well location if in city: of Topeka City, state, zip code:				6. Bore hole dia.	5	
4. Locate with "X" in section below: Sketch map:				6. Bore hole dia.	n. Completion date	_
4. Locate with "X" in section below: Sketch map: Well Septic 200 /- X						
Septil 2			7 Cable tool Rota		a rotony	
1'				B. Use:Domestic Public supply Industry		
				Irrigation Air conditioning Stock		
- 1005e				Lawn Oll field water Other		
				9. Casing: Material		ow
 				Threaded Welded RMP PVC <u>Q/</u>	Surface 24	in.
5 !===== 1 Mile =======				Dia. 5 in. to 120tt. d		
5. Type and color of material		From	То	Dia in. to ft. d		
				10. Screen: Manufacturer'	s name	
	TOP SOIL	0	4	Type RUC	Dig5	
				(Slot gauze 1020	Length	
¥	SROWN CLAY	4	35	Set between30	_fr. and <i>50</i>	ft.
Cou	rse sand	35	38	Gravel pack? Size	ond	<u>x.060</u>
				11. Static water level:		day/yr.
Shale	9Rey	38	60	_35_ft. below land :	surface Date 12-10-	76
Lime	STONE GREY	60	65	12. Pumping level below to		g.p.m.
Shall	ey Lime STONE	65	120	ft. after		
31,44	ey and a		/	Estimated maximum yield -		g.p.m.
				13. Water sample submitted	_	day/yr.
				Yes No 14. Well head completion:	CAP	
The state of the s				Pitless adapter	29 Inches above gr	ade
				15. Well grouted?		
				With: 1 Neat cement _ Depth: Fromft.		increte
						\dashv \land
			 	16. Neorest source of possi ft. 200 Direction	Type 5-4P	TIC
				Well disinfected upon com	oletion? Yes	— № T
				17. Pump:	Not installed	*
				Manufacturer's name Model number 554	A HP VZ Volts	<u>≥≥0</u> (√
				Length of drop pipe		.p.m. <6
				Туре:		· ·
				Submersible	Turbine Reciproce	ating
(Use a second	i sheet if needed)			Centrifugal	Other	ν
18. Elevation: 19. Remarks:				20. Water well contractor		let.
0.741				This well was drilled under	, .	eport _ S
Topography: Pu OWNER WILL INSTAL SLAD				is true to the best of my knowledge and belief. Steader Dolg Co. T.nc. 182		
Hill				Business name		se No 6
Slope				Address AT Ho	IN	
Upland				Signed Authorized	epresentative Date	575.78 D
Valley						<i>بر</i> اہ ہے۔