1 LOCATION OF WATER WELL:			Fraction	Fraction					r To	wnship Nu	lumber Range Number				
County:	Sha	wnee	NW	1/4	NE ½	. NE	1/4	30	Т	11	s	R		(E)W	
Distance and direction from nearest town or city street address of well if located within city?															
			Properties	LLC											
RR#, St. Address, Box # : PO Box 668 Board of Agriculture,													er Reso	ources	
City, State,	ZIP Code	: Manha	attan, KS	66505					Appl	ication Nu	mber:	47,105			
3 LOCATE	E WELL'S LOO N SECTION E	CATON WITH	4 DEDTU	OE COM	DI ETEN I	A/E1 1	70	4 ELE	NATION:						
	N SECTION E	SOA.					70								0
_			Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr										· ^{π.}	OFFICE	
	<u> </u>	X													띪
NWNE			Pump test data: Well water was ft. after hours pumping										gpm	USE	
	i	Est. Yield gpm: Well water was ft. after hours pumping										gpm	Ĭ		
<u></u> ₩		Bore Hole Diameter 30 in. to 70 ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below										ft.	SIN N		
1			WELL WAT	ER TO BI	E USED A	\S: 5 Pu	blic water su	ypply	8 Ai	ir condition	ning 1	1 Injection	well		'≺
	sw	SE	(a)	iestic 3	reed lot	6 011	field water s	supply	9 0	ewatering	12	2 Other (S)	эеспу в	elow)	
	i l	i I					wn and gard								
\ \	S		Was a chem	nical/bacte	eriological	l sample su									
			submitted					W							
_	F BLANK CAS				•	t Iron		ete tile		SING JOIN					
→ Ste		3 RMP	(SR)	6	Asbesto	s-Cement	9 Other	(specify belo	ow)		Weld	led			
(2) PV	С	4 ABS		7	Fibergla	ss		·			Threa	aded			
Blank casing	g diameter	16	in. to		_ft., Dia	70	in. t	0	ft., Dia	a		in. to		ft.	
Casing heig	ht above land	l surface	24	in., v	weight	16	3.150	lbs./ft.	. Wall thic	kness or	auge No.		.500		
TYPE OF S	CREEN OR F	PERFORATIO	ON MATERIAL less steel	.:	•		(7)	PVC		10 Asbe	stos-ceme	ent			
1 Ste	eel	3 Staini	ess steel	5	Fiberdia	SS	8 9	RMP (SR)		11 Othe	r (specify)				
2 Bra			inizoa otoor	6	Concrete	e tile	9	ABS		12 None	used (ope	en hole)			_
		TION OPENII				5 Gauze	d wrapped		(8) Sav	w cut		11 None	(open h	iole)	
!	ntinuous slot		Mill slot			6 wire w	rapped		9 Drii	llea noies					
	vered shutter		Key punched			7 Torch			10 Oth	ner (speci	ly)				
SCREEN-P	ERFORATED	INTERVALS					70								
			From		ft	. to	· · · · · <u></u> - · · ·	ft.	From		ft. t	to	.	ft.	æ
GRA	AVEL PACK I	NTERVALS:					70					to		ft.	
			From		ft	. to		ft.	From		ft. t			ft.	
6 GROUT	MATERIAL:	1 Neat	cement	2 Cer	nent grou	t	3 Ben	tonite	4 Other	r					
Grout Interv	als From	0	ft. to	20	ft. From		ft. t	0	ft.	From		ft. to		ft.	
What is the	nearest source	e of possible	contamination	1:				10 Lives	stock pen:	s	14 Ab	andoned wa	ater wel	1	
1 Sep	ptic tank	4 Lateral lines 7 Pit priv				• • •									
2 Sev	wer lines	5 Cess pool 8 Sewag									below)				
ì	itertight sewer	6 Seepage	e pit	9	Feedyard		13 Insecticide storage					e			
Direction fro								How many	y feet?						
FROM	TO	CODE		HOLOGI	C LOG		FROM	ТО		PLU	IGGING IN	NTERVALS			
0	1 10		urface	th fine				-							c.
10	10 18		Ity clay wi			with									SEC
10	10		ay lens	e mea	sailu V	VICII									
18	30	Fi	ne to med	sand	& grave	el			-						
30	69	Fi	ne to med	sand	& grave	el with		1	<u> </u>					$\overline{}$	
			obbles str		a grav	<u> </u>								$\overline{}$	
69	70		ack shale												
_1							<u> </u>	L							
		LANDOWNE	R'S CERTIFIC	CATION:	This water						-			I	
	on (mo/day/yr)			3/5/09			and thi								
Water Well	Contractor's L	license No.		3	34		This W	ater Well R	Record was	s complete	on (mo/	day/yr)	4/3/0	09	
under the bu	usiness name	of	W	oofter F	Pump 8			l	by (signat	ure)	our!	11/67	12		
INSTRI	UCTIONS: PI	ease fill in blank	ks and circle the	e correct a	nswers. S	end three co	pies to Kans	as Departme	ent of Healt	h and Envir	onment, Bu	reau of Wat	er, 1000	sw	