		WATE	ER WELL RECORD	Form WWC-5	5 KSA 82	a-1212			
1 LOCATION OF WAT		Fraction			ction Numbe		nber	Range Number	
County: SHAWNEE		SE 1/2			16	т 11	S	R 15E E/W	
Distance and direction		-	address of well if locate	ed within city?					
		est, 1 nort	h of Topeka						
WATER WELL OW	NER: Denr	nis Mohler							
RR#, St. Address, Box	· # : 5323	3 NW 25th				Board of Ag	riculture, Div	vision of Water Resources	
City, State, ZIP Code			618						
LOCATE WELL'S LO	OCATION WITH							,	
AN A IN SECTION	BOX.								
ī [ ]	ı	WELL'S STATIC	WATER LEVEL 3	31. <b>'</b> ft. t	pelow land su	urface measured on n	no/day/yr	2–19–91	
Pump test data: Well water was ft. after hours pumping gpm									
	1	Est. Yield 5	0. . gpm: Well wat	er was	ft	after	hours pum	ping gpm	
w i	Bore Hole Diameter . 8. 3/4. in. to							io	
w 1	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection						jection well		
-   sw	SE	1 Domestic						ther (Specify below)	
sw	36	2 Irrigation	4 Industrial	7 Lawn and	garden only	10 Monitoring well .			
i	1	Was a chemical	bacteriological sample	submitted to D	epartment?	/esNoX	; If yes, m	no/day/yr sample was sub-	
S		mitted		7.7	W	ater Well Disinfected	Yes X	No	
TYPE OF BLANK C	ASING USED:		5 Wrought iron	8 Concr	ete tile	CASING JOIN	TS: Glued	XClamped	
1 Steel	3 RMP (S	R)	6 Asbestos-Cement	9 Other	(specify belo	ow)	Welded	1	
2 PVC	4 ABS		7 Fiberglass				Thread	ed	
								. to ft.	
Casing height above la	ind surface	.24"	.in., weight 282	2	Ibs	./ft. Wall thickness or	gauge No.	.258	
TYPE OF SCREEN OF	R PERFORATIO	N MATERIAL:		7 PV	′C	10 Asbes	stos-cement	i e	
1 Steel 3 Stainless steel			5 Fiberglass	erglass 8 RMP (SR)			11 Other (specify)		
			6 Concrete tile				used (oper	n hole)	
SCREEN OR PERFOR	RATION OPENIN	5 Gauz	5 Gauzed wrapped		8 Saw cut		11 None (open hole)		
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutt	er 4 K	ley punched	7 Torch			, , , , , , , , , , , , , , , , , , , ,			
SCREEN-PERFORATE	D INTERVALS:								
From. ft. to ft., From ft. to .ft.   GRAVEL PACK INTERVALS: From. 24 ft. to .55 ft., From ft. to .ft.									
GRAVEL PAG	CK INTERVALS:								
1								ft.	
GROUT MATERIAL			-						
Grout Intervals: From0ft. to24 ft., Fromft. to ft., From ft. toft.									
What is the nearest source of possible contamination:								andoned water well	
1 Septic tank 4 Lateral lines					11 Fuel storage		15 Oil well/Gas well		
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit			9 Feedyard				any feet? 100 '		
Direction from well?	SE	1171101 0010		1 55014	<del></del>	arry root.	GGING INT	TEDVALC	
FROM TO	Mon Coil	LITHOLOGIC	LOG	FROM	ТО	PLU	GGING IN	EHVALS	
0 5	Top Soil			· - <del> </del> -	+ +				
5   30 30   35	Clay-Brow	d-Coarse Sa	nd-Prove						
35 46		d-Pea-Brown							
46 55		d-Pea 4-Bro							
40 33	Not to be		W11	1					
	NOT TO DE	a rock						** ** ** **	
				+	<del> </del>				
	THE RESIDENCE AND ADMINISTRATION OF THE PROPERTY.								
					<b></b>				
				i	<u> </u>				
T					L				
								my jurisdiction and was	
								vledge and belief. Kansas	
			This Water V	veil Record wa			17	han	
under the business nar	LIE OI STIVAL	VOI NUTTITI	O CO., IIVC.		by (signa	ature) Mult	1111	2011	