


1 LOCATION OF WATER WELL: Fraction NE 1/4 SE 1/4 SW 1/4 Section Number 16 Township Number T 11 S Range Number R 16 EW

Distance and direction from nearest town or city street address of well if located within city?
Well site @ 2639 Meriden Rd.

2 WATER WELL OWNER: Topeka Machinery Exchange
RR#, St. Address, Box #: 2851 SW Hodges Road Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Topeka, KS 66614 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 60' ft. ELEVATION: ...
Depth(s) Groundwater Encountered 1. 30' ft. 2. ... ft. 3. ... ft.
WELL'S STATIC WATER LEVEL: 16' ft. below land surface measured on mo/day/yr 11-10-95
Pump test data: Well water was ... ft. after ... hours pumping ... gpm
Est. Yield: 12 gpm; Well water was ... ft. after ... hours pumping ... gpm
Bore Hole Diameter: 12" in. to ... ft., and ... in. to ... ft.
WELL WATER TO BE USED AS:
5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes ... No ; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
7 Fiberglass Threaded
Blank casing diameter: 5" in. to 0-20 ft., Dia 5" in. to 35-59 ft., Dia ... in. to ... ft.
Casing height above land surface: 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 20 ft. to 35 ft., From ... ft. to ... ft.
From 59 ft. to 60 ft., From ... ft. to ... ft.
GRAVEL PACK INTERVALS: From 18 ft. to 60 ft., From ... ft. to ... ft.
From ... ft. to ... ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 18 ft., From ... ft. to ... ft., From ... ft. to ... ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? north How many feet? 220'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Top Soil			NOTE: 11-13-95 Permission to shallow grout from Don Taylor
4	15	Clay-Br-Silty			
15	30	Fine Sand-Brown			
30	37	Limestone-Grey			
37	41	Shale-Grey			
41	52	Limestone-Grey			
52	60	Shale-Grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-10-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 11-28-95 under the business name of STRADER DRILLING CO., INC. by (signature) Dale Hebron

OFFICE USE ONLY T R EW SEC 1/4 1/4 1/4