


1 LOCATION OF WATER WELL: County: SHAWNEE	Fraction SE 1/4 NW 1/4 NW 1/4	Section Number 26	Township Number T 11 S	Range Number R 16 E XX
--	----------------------------------	----------------------	---------------------------	--------------------------------------

Distance and direction from nearest town or city street address of well if located within city?
1.5 MILES WEST OF TECUMSEH KS. & 1.75 MILES NORTH

2 WATER WELL OWNER: CARL A. RICHARDS
 RR#, St. Address, Box # : 4211 SE HWY 40
 City, State, ZIP Code : TECUMSEH KS 66542
 Board of Agriculture, Division of Water Resources
 Application Number: 34701 & 41616

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 62 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 22 ft. 2. . ft. 3. . ft. WELL'S STATIC WATER LEVEL . 22 ft. below land surface measured on mo/day/yr 4-19-96 Pump test data: Well water was . 37 ft. after . 1 hours pumping 800 gpm Est. Yield . 1200 gpm: Well water was . 45 ft. after . 2 hours pumping 1000 gpm Bore Hole Diameter . 32 in. to . 62 ft., and . in. to . ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes . . . No. <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes . . . No <input checked="" type="checkbox"/>
---	--

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)
 7 Fiberglass
 Blank casing diameter . 16 in. to . 42 ft., Dia . in. to . ft., Dia . in. to . ft.
 Casing height above land surface . 12 in., weight . lbs./ft. Wall thickness or gauge No. . 50
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From . 42 ft. to . 62 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.
 GRAVEL PACK INTERVALS: From . 20 ft. to . 62 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From . 0 ft. to . 20 ft., From . ft. to . ft., From . ft. to . ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage . . . NONE
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	BLACK TOP SOIL			
1	13	FINE BROWN SANDY SILT			
13	16	MEDIUM-LARGE BROWN GRAVEL & GREY CLAY			
16	21	MEDIUM-BROWN GRAVEL			
21	39	MEDIUM GREY GRAVEL			
39	62	MEDIUM-LARGE GREEN GRAVEL & COBBLES			
	62	LARGE COBBLES , STOPPED			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) . 4-19-96 . . . and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. . 323 . . . This Water Well Record was completed on (mo/day/yr) . 5-7-96 . . . under the business name of HOUBLER DRILLING CO. by (signature) Daniel Hoobler

OFFICE USE ONLY