א מטנ וכט	10. 077 13	4		MATE	DWELL DE	00 <b>0</b> 0 F	1404/0 5	K04 00-	4040 ID A	- 00/1972		MW-9	
1 LOCATION	N OF WATE	R WELL:	Fraction		K WELL REG	CORD FO	m WWC-5	on Numbe		No. <b>0041872</b> Inship Number	Range	Number	
County:			NW		NE	14 SW	1/4	7	Т Т	<b>11</b> s	R	16 E	
Distance and	direction from	m nearest							<u> </u>		1	· · · · · · · · · · · · · · · · · · ·	
2640 NW F													
2 WATER W													
RR#, St. Addr					St., Ste. 4	110			Board	of Agriculture, Div	ision of Wat	er Resources	
City, State, ZI	P Code	: Top	eka, KS 6	6612					Applica	ation Number:			
3 AN "X" IN	VELL'S LOC SECTION B	OX:	T 4 DEPT	H OF C	OMPLETED	WELL	39	ft. ELE	VATION:	885	5.51 (TOC	;)	
<u> </u>			Depth(s)	Ground	water Encou	intered 1	30.	6	ft. 2	ft.	3	ft.	5
	NW	NE	WELL'S	STATIC	WATER LE	VEL 3	0.39 ft.	elow land	surface mea	asured on mo/day	/vr 08	3/07/07	CTTICE
1 1	ii l	1								hours			Ì
₩ W	+	-	E Est. Yield	1	gpm:	Well water	was		ft. after	hours	pumpina	apm	8
7	x	! I	Bore Hole	e Diame	ter 8	in. to	39		ft. and	conditioning vatering	n. to	ft.	SAL
	sw	SE	WELL W	ATER T	O BE USED	AS: 5 P	ublic water su	pply	8 Air	conditioning	11 Injection	well	-
↓ [				omestic	3 Feed R	ot 6 0	ii field water s	supply	9 Dev	vatering	12 Other (S	pecify below)	İ
	S						_	-		onitoring well			
			Was a ch		pacteriologic	cal sample s	submitted to D			No X If yes		sample was No <b>X</b>	
5 TYPE OF	BLANK CAS	ING USE			5 Wroug	iht Iron	8 Concre			NG JOINTS: Glu			1
1 Steel			P (SR)				9 Other (				ded		
2 PVC		4 AB			7 Fiberg						aded	Flush	1
Blank casing of				24	•		in to						1
Casing height	above land	surface	Flush	<del></del>	in weight		0.703	ihs/fl	Wall thick	ness or gauge No	S	CH. 40	
TYPE OF SCI	REEN OR PI	ERFORAT	ON MATERI	AL:	,,, wo.g		7	PVC	1	10 Asbestos-cem	ent		
1 Steel			inless steel										
2 Brass		4 Gal	vanized steel	l	6 Concre					11 Other (specify 2 None used (o			
SCREEN OR										cut	11 None	(open hole)	
	nuous slot	-	3 Mill slot				wrapped		9 Drille				
SCREEN-PER	ered shutter		4 Key punci		24	7 Torch			10 Otne	er (specify)			1
SOMELIN-PER	(FORATED	INTERVAL	.s. Floili							ft.			
GRA\	EL PACK IN	ITER\/AI S			21.5	ft to	39	<sup>1L.</sup>	From	ft.	to		:
0.01			From						From	"	to		
6 GROUT M	ATERIAL:	1 Ne	at cement	2	Cement are	out	3 Beni	onite	4 Other	Flowable Fi	II		
Grout Intervals	s From	21.5	ft to	16	ft From	n 1	6 # 1	1	l fi	From	ft to	ft	1
What is the ne							'6" '	10 Live	stock pens	14 A	bandoned w	ater well	
1 Septi	c tank		4 Latera	al lines		7 Pit privy			storage		il well/ Gas		
2 Sewe	er lines		5 Cess	pool		8 Sewage			tilizer storag		ther (specify	y below)	ļ
	rtight sewer	lines	6 Seepa	age pit		9 Feedyar	ď		ecticide stor	age			-
Direction from FROM	TO T	CODE		ITHOL	OGIC LOG		FROM	How mar	ny feet?	PLUGGING	INTEDVALO		4
0	0.2		Topsoil	LITHOL	OGIC LOG		FROM	10	+	PLUGGING	INTERVAL	,	┨
			Clay, silty,	dark b	rown to lig	ht brown							٦
0.2	26	t	o gray										
26	39		Sand, med	ium gra	ains, gray								4
						·		<del> </del>	<del> </del>				$\dashv$
							<del> </del>	<del>                                     </del>	+				$\dashv$
													$\Box$
													$\dashv$
													$\dashv$
7 CONTRAC	TOR'S OR	ANDOW	NER'S CERT	IFICATI	ON: This w	ater well wa	s (1) construc	ted, (2) re	constructed.	or (3) plugged ur	nder my juris	diction and was	$\exists$
completed on										best of my know			
Water Well Co					531					completed on (n			
under the bus	iness name	of	Geote		al Servi		by	(signature	e) 1	ed. 1			
INSTRUC	CTIONS: Ple	ase fill in bla	anks and circle	the corre	ect answers.	Send three	copies to Kans	as Departm	ent of Heal	and Environment,	Bureau of W	ater, 1000 S W	
Jackson	St., Ste. 420,	горека, Ка	nsas 66612-13	xo/. Tele	epnone: 913	-296-5545.	send one to W	A LER WEL	L OWNER ar	nd retain one for yo	ur records.		