				Div	ision of Wa	ter Reso	urces: App. No.	L				
		WATER WELL:										
County: Shawnee												
located wit	thin city?	2640 NW Topeka B	slvd, Topeka, KS	SE Section Number Township Number Range Number T 11 S R 16 E 17 S R 16 E 18 R R R R R R R R R								
	-	•	•		Longitude	: W						
2 WATE	RWELL	OWNER: Yingli	ng (NW Reo Project)		Elevation:	a b a		<u></u>				
City St	tate ZIP Co	ode : Z040 N	KS 66612		Datum: Data Colle	above ection M	lethod: legal	urvev				
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 43 ft.												
LOCA					AS-13							
WITH	AN "X" II	N Depth(s) Groun	ndwater Encountered 1			ft. 2		ft. 3	f			
SECTI	ON BOX:	WELL'S STA	ΓIC WATER LEVEL	ft	. below lar	nd surfa	ce measured o	n mo/d	ay/yr			
	N	Pum	test data: Well water	was	ft.	after	hours	pumpi	ng gpi			
		Est. Yield	gpm: Well water	was	ft.	after	hours	pumpi	ng gpi			
-NW	- NE -	WELL WATE	R TO BE USED AS: 5	Public wa	ter supply	8 Air	r conditioning		ijection well			
w		E Domestic 3	Feed lot 6 Oil field v	vater supp	iy rardan) l	9 Dewa	atering (U Oth	er (Specify below			
	<u></u>	2 irrigation 4	industrial / Domestic	(lawn & g	garden) i	U MIOIII	noring wen		Air Sparge			
Fsw	Was a chemical/hacteriological sample submitted to Department? Ves No X : If yes mo/day/yrs											
<u> </u>	S	Sample was su	bmitted	Submittee	V	Vater W	ell Disinfected	i? Yes	No X			
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped												
1 Stee	el CASII	3 RMP (SR) 6	Asbestos-Cement	9 Other (specify be	low)		Welde	d			
(2) PV	C 4	4 ABS 7	Fiberglass	, , , , , ,	specific series	,		Thread	ied X			
Blank casi	ng diamete	r 2 in. to	40 ft., Dia	i	n. to 42-	43 ft.,	Dia	in.	to			
Casing heigh	Casing height below land surface ft., Weight lbs./ft. Wall thickness or gauge No.											
TYPE OF	SCREEN (RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded ABS 7 Fiberglass Threaded X 2 in. to 40 ft., Dia in. to 42-43 ft., Dia in. to ft. d surface ft., Weight Ibs./ft. Wall thickness or gauge No. R PERFORATION MATERIAL: less steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) unized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) RATION OPENINGS ARE: 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) er 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) ED INTERVALS: From 40 ft. to 42 ft. From ft. to ft. From ft. to ft. From ft. to ft.										
1 Ste	Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) EN OR PERFORATION OPENINGS ARE: Continuous slot 6 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)											
SCREEN (ISS 4 Gaiv	Stainless steel 5 Fiberglass (1) PVC 9 ABS 11 Other (specify) Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) RFORATION OPENINGS ARE: is slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) DRATED INTERVALS: From 40 ft. to 42 ft. From ft. to ft. From ft. to ft. From ft. to ft. PACK INTERVALS: From 33 ft. to 43 ft. From ft. to ft.										
1 Cor	ntinuous slo	ot (3) Mill slot	Fraction									
2 Lou	ivered shut	ter 4 Key punche	Submitted Water Well Disinfected? Yes No X 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X 40 ft., Dia in. to 42-43 ft., Dia in. to ft. ft., Weight Ibs./ft. Wall thickness or gauge No. ON MATERIAL: Fiberglass 7 PVC 9 ABS 11 Other (specify) Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) INGS ARE: 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) thed 6 Wire wrapped 8 Saw Cut 10 Other (specify) LS: From 40 ft. to 42 ft. From ft. to ft. From ft. to ft. From ft. to ft. From 33 ft. to 43 ft. From ft. to ft. wement 2 Cement grout 3 Bentonite 4 Other Cement: 0-27 ft. to 33 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. contamination: lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify)									
SCREEN-	PERFORA	TED INTERVALS	: From 40	ft. to	42	. ft. Fro	om	ft. t	0			
(CD	ATTEL DAG	TE TAITED VALO.	From	π. το	42	π. Fro	om	π. τ	0			
GK	AVEL PAC	CK INTERVALS:	From 33	ft. to	43	ft. Fr	om	il. i ft t	0			
			110111	(2)	:	10. 110	O 2	7.04	·			
6 GROU	T MATER	RIAL: Neat cer	nent 2 Cement grout	Bento	onite (2	Other	Cement: 0-2	/ It.	ft to fi			
Grout Intervals From 27 ft. to 33 ft. From ft. to ft. From ft. to ft. From ft. to ft.												
1 Sent	What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify											
	er lines	lines 5 Cess pool 8 Sewage lagoon 1 Fuel storage 14 Abandoned water well below)										
3 Wat	ertight sew	er lines 6 Seepage				15 Oil	well/ gas well					
Direction	from well?			How many	feet?							
FROM	TO	LITHO	LOGIC LOG	FROM	TO		PLUGGIN	G INT	ERVALS			
0	1	Asphalt										
1	14											
25	25 39			-	+	<u> </u>						
39	43											
				-	-	Flushn	nount waiver	from F	BOW			
7 CONTI	RACTOR'	n from nearest town or city street address of well if Cato Postitioning System (decimal degrees, min. of 4 digits) Latitude: N Longitude: N Longitud										
under my jurisdiction and was completed on (mo/day/year) 10/1/08 and this record is the best of my knowledge and belief												
Kansas Water Well Contractor's License No. 757 . This Water Well Record was completed on (pro/day/year) 12/29/08												
under the business name of Larsen and Associates, Inc. by (signature) INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send ton three copies to Kansas Department Mealth and Environment. Bureau of Water.												
Geology Section 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367, Telephone 785-296-5522, Send one to WATER WELL OWNER and retain one for												
your records.	Fee of \$5.00	for each constructed we	your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.									