WATER WELL RECORD	Form W			r Resources App. No		
1 LOCATION OF WATER WE County: Sedawick	CLL: Fraction NE 1/4 SE 1/4 SW	S 1/4 S	ection Number	Township No. T 26 S	Range Number R / ∑ E □W	
Street/Rural Address of Well Lo			lobal Positioning	System (GPS) in		
from nearest town or intersection: If at owner's address, check here \(\mathbb{K} \) .		here 况. L	Latitude:			
, trade		L	Longitude: (in decimal degrees)			
•			Elevation:			
2 WATER WELLOWNER: CHUSTAL SPICET			Datum: WGS 84, NAD 83, NAD 27 Collection Method:			
RR#, Street Address, Box #: 6358 Al. Cam OOS Lo			GPS unit (Make/Model:)			
2 WATER WELL OWNER: Crystal Spicer RR#, Street Address, Box #: 6358 N. Campos Ln City, State, ZIP Code : Wichiba , KS			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
			- WHI VALUE OF THE STATE OF THE		3-13 m, □ >13 m	
WITH AN "X" IN 4 DEP	TH OF COMPLETED WELL	ι5 <i>0</i>	ft.			
SECTION BOX: Depth(s)	ION BOX: Depth(s) Groundwater Encountered (1). ft. (2)					
N WELL'S	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr					
Pump test data: Well water was						
W -NW NE - EST. YIELDgpm Well water wasft. after						
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well						
Domestic						
Irrigation Industrial Domestic-lawn & garden Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No						
S If yes, mo/day/yr sample was submitted						
Witter were districted.						
5 TYPE OF CASING USED: Steel V PVC Other						
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter						
Casing height above land surface						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel ☐ Stainless Steel ☐ Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From. 40 ft. to 50 ft., From ft. to ft.						
From. ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft.						
Fromft. to						
6 CROUT MATERIAL: Neat cement Cement grout Bentonite Other						
Grout Intervals: From ft. to ft. to ft., From ft. to ft., From ft. to ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:						
Septic tank Sewer lines						
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well						
Direction from well North Distance from well 105.						
	THOLOGIC LOG	FROM T	O LITHO. I	OG (cont.) or PLU	UGGING INTERVALS	
0 2 Topsoi						
2 14 Clay						
14 26 Sandy 26 32 Green	Claye					
26 32 Green 32 50 Med	Sand	+				
7 CONTRACTORS OF LAND	OWNER'S CEDTIFICATIO	No. This water s	well was VI const	tructed Treconst	ructed, or \square nlugged	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 12 1.11 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's L	icense No This	Water Well Rec	ord was complete	ed on (mo/day/yea:	r) (2-f 2 . Q. f . ! . (
under the business name of (IAAA) () A4 (IAAA) by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at						
http://www.kdheks.gov/waterwell/index.html,						
KSA 82a-1212						