WATER WELL RECORD Form WWC-5	Division of Water Resources; App. No.
1 LOCATION OF WATER WELL: Fraction County: Shawnee NE 1/2 NE 1/2 SW 1/2 Distance and direction from nearest town or city street address of well is	Section Number Township Number Range Number T 11 S R 16 E
Distance and direction from nearest town or city street address of well i located within city? 817 SW Harrison St, Topeka, KS 66603	Latitude: N 39.04908
2 WATER WELL OWNER: Tim Roark (Kwik Shop, Inc.)	Longitude: W ° 95.680731 Elevation: RIM: 934.89; TOC: 934.58
RR#, St. Address, Box # : PO Box 1927	Datum: NAVD88
City, State, ZIP Code : Hutchinson, KS 67504-1927	Data Collection Method: legal survey
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 9.6	
LOCATON	MW13
WITH AN "X" IN Depth(s) Groundwater Encountered 1	ft. 2 ft. 3 ft.
CECTION DOV: 10/H1 1/2 STATIC WATER LEVEL X /II	TO DETOW TARGESTITACE REGASTICE OF THO/ GRAY/ YE - S/ #4/ 12
N Pump test data: Well water was	ft. after hours pumping gpm ft. after hours pumping gpm gpm gpm
Est. Yield gpm: Well water was	c water supply 8 Air conditioning 11 Injection well
	supply 9 Dewatering 12 Other (Specify below)
W E 1 Domestic 3 Feed lot 6 Oil field water 2 Irrigation 4 Industrial 7 Domestic (lawr	a & garden) (10) Monitoring well
	(to gui uon)
SW SE Was a chemical/bacteriological sample subm	nitted to Department? Yes No X; If yes, mo/day/yrs
S Sample was submitted	Water Well Disinfected? Yes No X
5 TYPE OF CASING USED: 5 Wrought Iron 8 Co	ncrete tile CASING JOINTS: Glued Clamped
1 Steel 2 DMD (CD) 6 Ashestos Cement 9 Otl	her (specify helow) Welded
PVC 4 ABS 7 Fiberglass	Threaded X
Blank casing diameter 2 in to 3 ft., Dia	in. to ft., Dia in. to ft.
2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 3 ft., Dia Casing height below land surface 0.31 ft., Weight	lbs./ft. Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:	11.01. (
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR)	9 ABS 11 Other (specify)
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7	Forch cut 9 Drilled holes 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 8	Saw Cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 3 ft. to	o 9.60 ft. From ft. to ft.
From ft. t	o ft. From ft. to tt.
GRAVEL PACK INTERVALS: From 2 ft. to	0 9.90 ft. From ft. to ft.
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 SCREEN-PERFORATED INTERVALS: From 3 ft. tr From ft. tr GRAVEL PACK INTERVALS: From 2 ft. tr From ft. tr	o tt. From tt. to tt.
6 CPOUT MATERIAL: 1 Neat cement 2 Cement grout [3]	Bentonite (4)Other Concrete: 0-1 It
Grout Intervals From 1 ft. to 2 ft. From ft. to ft. From ft. to ft.	
What is the nearest source of possible contamination:	
	vestock pens 13 Insecticide Storage 16 Other (specify lel storage 14 Abandoned water well below)
2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fu 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fe	ertilizer storage 15 Oil well/ gas well
Direction from well? NW	many feet? ~225 ft
	ROM TO PLUGGING INTERVALS
TROM TO BITTODO OLO	TEOGOTIVO INTERVINES
0 9.90 Soft brown silty clay Limestone bedrock at 9.90 feet	
Zimestowe settletists	
	Flushmount waiver from BOW
	(2) manufacturated on (2) almost
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: under my jurisdiction and was completed on (mo/day/year) 4/30/12	and this record is true to the best of my knowledge and belief
under my jurisdiction and was completed on $(mo/day/year)$	/ell Record was completed on (mo/day/year)5/30/12
under the business name of Larsen & Associates, Inc. by (signature)
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three c	copies to Kansas Department of Health and Environment, Bureau of Water,
Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66(12-1367). Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for	