

1 LOCATION OF WATER WELL  
 County: SHAWNEE Fraction: NE 1/4 NE 1/4 NW 1/4 Section Number: 27 Township Number: T 11 S Range Number: R 16 E

Distance and direction from nearest town or city? Street address of well if located within city?  
Hy. 24 EAST

2 WATER WELL OWNER: MR. TATE  
 RR#, St. Address, Box #: Hy 24 E Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: TOPEKA KAN. 66608 Application Number:


3 DEPTH OF COMPLETED WELL: 37 ft. Bore Hole Diameter: 8 in. to 23 ft., and 5 in. to 37 ft.  
 Well Water to be used as:  
 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well  
 2 Irrigation 4 Industrial DP 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)  
WATER FOR LIVE BAIT  
 Well's static water level: 23 ft. below land surface measured on 5 month 15 day 81 year  
 Pump Test Data: Well water was 36 ft. after 1 hours pumping 16 gpm  
 Est. Yield 30 gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: Glued  Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing dia 5 in. to 32 ft., Dia in. to ft., Dia in. to ft.  
 Casing height above land surface: 24 in., weight lbs./ft. Wall thickness or gauge No 160  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)  
 9 ABS 12 None used (open hole)  
 Screen or Perforation Openings Are:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 Screen-Perforation Dia: 1/4 in. to 37 ft., Dia 5 in. to 32 ft., Dia in. to ft.  
 Screen-Perforated Intervals: From 32 ft. to 37 ft., From ft. to ft.  
 Gravel Pack Intervals: From ft. to ft., From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grouted Intervals: From 1 ft. to 21 ft., From ft. to ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well  
 2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well  
 3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below)  
 13 Watertight sewer lines  
 Direction from well: SW How many feet: 120? Water Well Disinfected? Yes  No  
 Was a chemical/bacteriological sample submitted to Department? Yes No  If yes, date sample was submitted month day year Pump Installed? Yes No  
 If Yes: Pump Manufacturer's name: BURKS Model No. ASN 136B HP 1/3 Volts 115  
 Depth of Pump Intake: 33 ft. Pumps Capacity rated at 10 gal./min.  
 Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 5 month 15 day 81 year and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 333  
 This Water Well Record was completed on 5 month 19 day 81 year under the business name of H.L. PETTIT by (signature) H.L. Pettit

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	TOP SOIL			
4	10	BROWN EARTH			
10	18	" SILT			
18	26	SAND + SILT			
26	37	SAND + GRAVEL			

ELEVATION:

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY  
T  
R  
16  
BW  
SEC  
27  
16 1/4  
NE 1/4  
NW 1/4