

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

NW-NE-SE

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:		County SHAWNEE	Fraction NW-NE-SE 1/4	Section number 28	Township number T 11 S R 16 E 10	Range number
2. Distance and direction from nearest town or city: Street address of well location if in city: 727 ARTER			3. Owner of well: MYRON BARKER R.R. or street: 727 ARTER City, state, zip code: TOPEKA KAN. 66616			
4. Locate with "X" in section below: N W E S 1 Mile		Sketch map: 		6. Bore hole dia. 8 in. Completion date 7-16-76 Well depth 49 ft.		
5. Type and color of material		From	To	7. Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> <input type="checkbox"/> Hollow rod <input checked="" type="checkbox"/> Jetted <input checked="" type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
Top soil		0	6	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input checked="" type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
HARD PAN CLAY		6	10	9. Casing: Material <input type="checkbox"/> Height: Above <input type="checkbox"/> Below <input checked="" type="checkbox"/> Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 14 in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight <input type="checkbox"/> lbs./ft. Dia. 5 in. to 49 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 200		
BROWN SILT		10	16	10. Screen: Manufacturer's name SUNFLOWER Type <input type="checkbox"/> Dia. <input checked="" type="checkbox"/> Slot/gauge 1/4 " Length 5 ' Set between 44 (ft.) and 49 (ft.) 24 ft. and <input type="checkbox"/> ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/4 "		
CLAY DROWN		16	28	11. Static water level: <input type="checkbox"/> mo./day/yr. 30 ft. below land surface Date 7-16-76		
SAND FINE		28	33	12. Pumping level below land surfaces: 30 ft. after 2 hrs. pumping 16 g.p.m. <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 20 g.p.m.		
GRAVEL		33	36	13. Water sample submitted: <input type="checkbox"/> mo./day/yr. <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>		
FINE SAND		36	44	14. Well head completion: <input type="checkbox"/> Pitless adapter 14 " inches above grade		
GRAVEL + SAND		44	49	15. Well grouted? <input checked="" type="checkbox"/> With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 1 ft. to 11 ft.		
				16. Nearest source of possible contamination: ft. 30 Direction SW Type SEWER Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: <input type="checkbox"/> Not installed Manufacturer's name GOULD Model number 7E7 HP 1/2 Volts 115 Length of drop pipe 42 ft. capacity 10 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation: 878 <i>rem</i>		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. H.L. PETTIT 333 Business name 905 N MICHIGAN License No. Address H.L. Pettit Signed H.L. Pettit Date 7-30-76 Authorized representative		

11 16 0 28 SE SE NE